






Test Report issued under the responsibility of:



<b>TEST REPORT</b> <b>IEC 62133-2</b> <b>Secondary cells and batteries containing alkaline or other non-acid electrolytes – Safety requirements for portable sealed secondary cells, and for batteries made from them, for use in portable applications –</b> <b>Part 2: Lithium systems</b>	
<b>Report Number</b> .....	EFSH23090237-IE-01-L01
<b>Date of issue</b> .....	2023-02-04
<b>Total number of pages</b> .....	39 Pages
<b>Name of Testing Laboratory preparing the Report</b> .....	Eurofins Electrical Testing Service (Shanghai) Co., Ltd
<b>Applicant's name</b> .....	GlobTek, Inc.
<b>Address</b> .....	186 Veterans Drive Northvale, NJ 07647 United States of America
<b>Test specification:</b>	
<b>Standard</b> .....	IEC 62133-2:2017
<b>Test procedure</b> .....	CB Scheme
<b>Non-standard test method</b> .....	N/A
<b>Test Report Form No.</b> .....	IEC62133_2A
<b>Test Report Form(s) Originator</b> .....	DEKRA
<b>Master TRF</b> .....	Dated 2017-08-10
<b>Copyright © 2017 IEC System of Conformity Assessment Schemes for Electrotechnical Equipment and Components (IECEE System). All rights reserved.</b>	
This publication may be reproduced in whole or in part for non-commercial purposes as long as the IECEE is acknowledged as copyright owner and source of the material. IECEE takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.	
If this Test Report Form is used by non-IECEE members, the IECEE/IEC logo and the reference to the CB Scheme procedure shall be removed.	
<b>This report is not valid as a CB Test Report unless signed by an approved CB Testing Laboratory and appended to a CB Test Certificate issued by an NCB in accordance with IECEE 02.</b>	
<b>General disclaimer:</b>	
The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Issuing CB Testing Laboratory. The authenticity of this Test Report and its contents can be verified by contacting the NCB, responsible for this Test Report.	

<b>Test item description</b> .....	Lithium-Ion Battery Pack	
<b>Trade Mark</b> .....		
<b>Manufacturer</b> .....	GlobTek, Inc. 186 Veterans Drive Northvale, NJ 07647 United States of America	
<b>Model/Type reference</b> .....	BL0950CAA652S1P****, BL0950C146502S1P****(* May be A~Z or 0~9 or blank for marketing purposes),	
<b>Ratings</b> .....	7.4 V, 950 mAh, 7,03 Wh	
<b>Responsible Testing Laboratory (as applicable), testing procedure and testing location(s):</b>		
<input checked="" type="checkbox"/>	<b>CB Testing Laboratory:</b>	Eurofins Electrical Testing Service (Shanghai) Co., Ltd
	<b>Testing location/ address</b> .....	Building 18, No. 2168 Chenhang Highway, Minhang District, Shanghai, China
	<b>Tested by (name, function, signature)</b> .....	Pengcheng Wang / Project Engineer 
	<b>Approved by (name, function, signature)</b> ..	Jackie Zhao / Project Engineer 
<input type="checkbox"/>	<b>Testing procedure: CTF Stage 1:</b>	
	<b>Testing location/ address</b> .....	
	<b>Tested by (name, function, signature)</b> .....	
	<b>Approved by (name, function, signature)</b> ..	
<input type="checkbox"/>	<b>Testing procedure: CTF Stage 2:</b>	
	<b>Testing location/ address</b> .....	
	<b>Tested by (name + signature)</b> .....	
	<b>Witnessed by (name, function, signature)</b> ..	
	<b>Approved by (name, function, signature)</b> ..	
<input type="checkbox"/>	<b>Testing procedure: CTF Stage 3:</b>	
<input type="checkbox"/>	<b>Testing procedure: CTF Stage 4:</b>	
	<b>Testing location/ address</b> .....	
	<b>Tested by (name, function, signature)</b> .....	
	<b>Witnessed by (name, function, signature)</b> ..	
	<b>Approved by (name, function, signature)</b> ..	
	<b>Supervised by (name, function, signature)</b> :	

**List of Attachments (including a total number of pages in each attachment):**

Attachment I: (Republic of Korea) NATIONAL DIFFERENCES (3 pages)

Attachment II: Photos (10 pages)

**Summary of testing:**

The product covered by this report has been tested and complies with the applicable requirements of this standard.

**Tests performed (name of test and test clause):**

- Clause 7.2.1 Continuous charging at constant voltage (cells)
- Clause 7.2.2 Case stress at high ambient temperature (battery)
- Clause 7.3.1 External short circuit (cells)
- Clause 7.3.2 External short circuit (batteries)
- Clause 7.3.3 Free fall
- Clause 7.3.4 Thermal abuse (cells)
- Clause 7.3.5 Crush (cells)
- Clause 7.3.6 Over-charging of battery
- Clause 7.3.7 Forced discharge (cells)
- Clause 7.3.8.1 Vibration (battery)
- Clause 7.3.8.2 Mechanical shock (battery)

**Testing location:**

Eurofins Electrical Testing Service (Shanghai)  
Co., Ltd  
Building 18, No. 2168 Chenhang Highway, Minhang  
District, Shanghai, China

**Summary of compliance with National Differences (List of countries addressed):**

EU Group: no differences


GB: No differences

KR: South Korea

**The product fulfils the requirements of IEC 62133-2:2017, EN 62133-2:2017, BS EN 62133-2:2017, KC 62133-2(2020-7).**

**Copy of marking plate:**

The artwork below may be only a draft. The use of certification marks on a product must be authorized by the respective NCBS that own these marks.



<b>Test item particulars</b> .....	Rechargeable Li-ion battery
<b>Classification of installation and use</b> .....	To be used in final product
<b>Supply Connection</b> .....	Supplied by DC connector
<b>Recommend charging method declared by the manufacturer</b> .....	CC/CV
<b>Discharge current (0,2 It A)</b> .....	190 mA
<b>Specified final voltage</b> .....	6 V
<b>Upper limit charging voltage per cell</b> .....	4,2 V
<b>Maximum charging current</b> .....	950 mA
<b>Charging temperature upper limit</b> .....	45 °C
<b>Charging temperature lower limit</b> .....	0 °C
<b>Polymer cell electrolyte type</b> .....	<input type="checkbox"/> gel polymer <input type="checkbox"/> solid polymer <input checked="" type="checkbox"/> N/A
<b>Possible test case verdicts:</b>	
- test case does not apply to the test object.....	: N/A
- test object does meet the requirement.....	: P (Pass)
- test object does not meet the requirement.....	: F (Fail)
<b>Testing</b> .....	
<b>Date of receipt of test item</b> .....	: 2023-09-21
<b>Date (s) of performance of tests</b> .....	: 2023-12-01 to 2023-12-29
<b>General remarks:</b>	
<p>The test results presented in this report relate only to the object tested.</p> <p>This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.</p> <p>"(See Enclosure #)" refers to additional information appended to the report.</p> <p>"(See appended table)" refers to a table appended to the report.</p> <p><b>Throughout this report a <input checked="" type="checkbox"/> comma / <input type="checkbox"/> point is used as the decimal separator.</b></p> <p>The related applicable CTL decisions have been considered and the requirements found fulfilled</p> <p>Determination of the test result includes consideration of measurement uncertainty from the test equipment and methods.</p>	
<b>Manufacturer's Declaration per sub-clause 4.2.5 of IEC 60335-1:</b>	
The application for obtaining a CB Test Certificate includes more than one factory location and a declaration from the Manufacturer stating that the sample(s) submitted for evaluation is (are) representative of the products from each factory has been provided.....	<input type="checkbox"/> <b>Yes</b> <input checked="" type="checkbox"/> <b>Not applicable</b>
<b>When differences exist; they shall be identified in the General product information section.</b>	
<b>Name and address of factory (ies)</b> .....	GlobTek (Suzhou) Co., Ltd. Building 4, No. 76 JinLing East Road, Suzhou Industrial Park, Suzhou, JiangSu, 215021, China

**General product information and other remarks:**

This battery is constructed with two rechargeable Li-ion cells in 2S1P, and PCB circuit, provides with overcharge, over-discharge, short-circuits proof circuit as part of protection effect.


BL0950CAA652S1P\*\*\*\* and BL0950C146502S1P\*\*\*\* are identical except for different printed circuit board. After review, BL0950CAA652S1P\*\*\*\* was subjected to all applicable tests and the most unfavourable data was recorded. BL0950C146502S1P\*\*\*\* was subjected to the test of Cl.7.3.2, Cl.7.3.6.

**Parameters:**


Nominal capacity	950 mAh
Nominal voltage	7,4 V
Nominal charge current	190 mA
Nominal discharge current	190 mA
Maximum charge current	950 mA
Maximum discharge current	950 mA
Upper limit charging voltage	8,4 V
Cut-off voltage	6 V
Operating temperature	0-45 °C

**Circuit diagram:**

BL0950CAA652S1P\*\*\*\*



BL0950C146502S1P\*\*\*\*



IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
<b>4</b>	<b>PARAMETER MEASUREMENT TOLERANCES</b>		<b>P</b>
	Parameter measurement tolerances		P
<b>5</b>	<b>GENERAL SAFETY CONSIDERATIONS</b>		<b>P</b>
<b>5.1</b>	<b>General</b>		P
	Cells and batteries so designed and constructed that they are safe under conditions of both intended use and reasonably foreseeable misuse		P
<b>5.2</b>	<b>Insulation and wiring</b>		P
	The insulation resistance between the positive terminal and externally exposed metal surfaces of the battery (excluding electrical contact surfaces) is not less than 5 MΩ		N/A
	Insulation resistance (MΩ) ..... :		—
	Internal wiring and insulation are sufficient to withstand maximum anticipated current, voltage and temperature requirements		P
	Orientation of wiring maintains adequate clearance and creepage distances between conductors		P
	Mechanical integrity of internal connections accommodates reasonably foreseeable misuse		P
<b>5.3</b>	<b>Venting</b>		P
	Battery cases and cells incorporate a pressure relief mechanism or are constructed so that they relieve excessive internal pressure at a value and rate that will preclude rupture, explosion and self-ignition		P
	Encapsulation used to support cells within an outer casing does not cause the battery to overheat during normal operation nor inhibit pressure relief		N/A
<b>5.4</b>	<b>Temperature, voltage and current management</b>		P
	Batteries are designed such that abnormal temperature rise conditions are prevented		P
	Batteries are designed to be within temperature, voltage and current limits specified by the cell manufacturer		P
	Batteries are provided with specifications and charging instructions for equipment manufacturers so that specified chargers are designed to maintain charging within the temperature, voltage and current limits specified		P
<b>5.5</b>	<b>Terminal contacts</b>		P
	The size and shape of the terminal contacts ensure that they can carry the maximum anticipated current		P



IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
	External terminal contact surfaces are formed from conductive materials with good mechanical strength and corrosion resistance		P
	Terminal contacts are arranged to minimize the risk of short-circuit		P
<b>5.6</b>	<b>Assembly of cells into batteries</b>		P
5.6.1	General		P
	Each battery have an independent control and protection for current, voltage, temperature and any other parameter required for safety and to maintain the cells within their operating region	Overcharge, over discharge, over current and short-circuit proof circuit used in this battery	P
	This protection may be provided external to the battery such as within the charger or the end devices		N/A
	If protection is external to the battery, the manufacturer of the battery provide this safety relevant information to the external device manufacturer for implementation		N/A
	If there is more than one battery housed in a single battery case, each battery have protective circuitry that can maintain the cells within their operating regions		P
	Manufacturers of cells specify current, voltage and temperature limits so that the battery manufacturer/designer may ensure proper design and assembly	Current, voltage and temperature limits specified by cell manufacturer.	P
	Batteries that are designed for the selective discharge of a portion of their series connected cells incorporate circuitry to prevent operation of cells outside the limits specified by the cell manufacturer		N/A
	Protective circuit components added as appropriate and consideration given to the end-device application		P
	The manufacturer of the battery provide a safety analysis of the battery safety circuitry with a test report including a fault analysis of the protection circuit under both charging and discharging conditions confirming the compliance		P
5.6.2	Design recommendation		P
	For the battery consisting of a single cell or a single cellblock, it is recommended that the charging voltage of the cell does not exceed the upper limit of the charging voltage specified in Table 2		N/A

IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
	For the battery consisting of series-connected plural single cells or series-connected plural cellblocks, it is recommended that the voltages of any one of the single cells or single cellblocks does not exceed the upper limit of the charging voltage, specified in Table 2, by monitoring the voltage of every single cell or the single cellblocks		P
	For the battery consisting of series-connected plural single cells or series-connected plural cellblocks, it is recommended that charging is stopped when the upper limit of the charging voltage is exceeded for any one of the single cells or single cellblocks by measuring the voltage of every single cell or the single cellblocks		P
	For batteries consisting of series-connected cells or cell blocks, nominal charge voltage not be counted as an overcharge protection		P
	For batteries consisting of series-connected cells or cell blocks, cells have closely matched capacities, be of the same design, be of the same chemistry and be from the same manufacturer		P
	It is recommended that the cells and cell blocks not discharged beyond the cell manufacturer's specified final voltage		P
	For batteries consisting of series-connected cells or cell blocks, cell balancing circuitry incorporated into the battery management system		P
5.6.3	Mechanical protection for cells and components of batteries		P
	Mechanical protection for cells, cell connections and control circuits within the battery provided to prevent damage as a result of intended use and reasonably foreseeable misuse	Mechanical protection for cell connections and control circuits provided.	P
	The mechanical protection can be provided by the battery case or it can be provided by the end product enclosure for those batteries intended for building into an end product		P
	The battery case and compartments housing cells designed to accommodate cell dimensional tolerances during charging and discharging as recommended by the cell manufacturer		P
	For batteries intended for building into a portable end product, testing with the battery installed within the end product considered when conducting mechanical tests		N/A
<b>5.7</b>	<b>Quality plan</b>		P

IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
	The manufacturer prepares and implements a quality plan that defines procedures for the inspection of materials, components, cells and batteries and which covers the whole process of producing each type of cell or battery	ISO 9001	P
<b>5.8</b>	<b>Battery safety components</b>		P
	According annex F		P

<b>6</b>	<b>TYPE TEST AND SAMPLE SIZE</b>		<b>P</b>
	Tests are made with the number of cells or batteries specified in Table 1 using cells or batteries that are not more than six months old		P
	Coin cells with resistance $\leq 3 \Omega$ (measured according annex D) are tested according table 1	Not coin cells	N/A
	Unless otherwise specified, tests are carried out in an ambient temperature of $20 \text{ }^\circ\text{C} \pm 5 \text{ }^\circ\text{C}$		P
	The safety analysis of 5.6.1 identify those components of the protection circuit that are critical for short-circuit, overcharge and overdischarge protection		P
	When conducting the short-circuit test, consideration given to the simulation of any single fault condition that is likely to occur in the protecting circuit that would affect the short-circuit test	See clause 7.3.2.	P

<b>7</b>	<b>SPECIFIC REQUIREMENTS AND TESTS</b>		<b>P</b>
<b>7.1</b>	<b>Charging procedure for test purposes</b>		P
7.1.1	First procedure		N/A
	This charging procedure applies to subclauses other than those specified in 7.1.2		N/A
	Unless otherwise stated in this document, the charging procedure for test purposes is carried out in an ambient temperature of $20 \text{ }^\circ\text{C} \pm 5 \text{ }^\circ\text{C}$ , using the method declared by the manufacturer		N/A
	Prior to charging, the battery have been discharged at $20 \text{ }^\circ\text{C} \pm 5 \text{ }^\circ\text{C}$ at a constant current of 0.2 It A down to a specified final voltage		N/A
7.1.2	Second procedure		P
	This charging procedure applies only to 7.3.1, 7.3.4, 7.3.5, and 7.3.9		P

IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
	After stabilization for 1 h and 4 h, respectively, at ambient temperature of highest test temperature and lowest test temperature, as specified in Table 2, cells are charged by using the upper limit charging voltage and maximum charging current, until the charging current is reduced to 0.05 It A, using a constant voltage charging method		P
<b>7.2</b>	<b>Intended use</b>		P
7.2.1	Continuous charging at constant voltage (cells)		N/A
	Fully charged cells are subjected for 7 days to a charge using the charging method for current and standard voltage specified by the cell manufacturer		N/A
	Results: No fire. No explosion. No leakage ..... :		N/A
7.2.2	Case stress at high ambient temperature (battery)		P
	Oven temperature (°C)..... : 70		--
	Results: No physical distortion of the battery case resulting in exposure of internal protective components and cells		P
<b>7.3</b>	<b>Reasonably foreseeable misuse</b>		P
7.3.1	External short-circuit (cell)		N/A
	The cells were tested until one of the following occurred:		N/A
	- 24 hours elapsed; or		N/A
	- The case temperature declined by 20 % of the maximum temperature rise		N/A
	Results: No fire. No explosion ..... :		N/A
7.3.2	External short-circuit (battery)	Tested complied.	P
	The batteries were tested until one of the following occurred:		P
	- 24 hours elapsed; or		P
	- The case temperature declined by 20 % of the maximum temperature rise		N/A
	In case of rapid decline in short circuit current, the battery pack remained on test for an additional one hour after the current reached a low end steady state condition		N/A
	A single fault in the discharge protection circuit conducted on one to four (depending upon the protection circuit) of the five samples before conducting the short-circuit test		P
	A single fault applies to protective component parts such as MOSFET, fuse, thermostat or positive temperature coefficient (PTC) thermistor		P

IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
	Results: No fire. No explosion .....	(See appended table 7.3.2)	P
7.3.3	Free fall	Tested complied.	P
	Results: No fire. No explosion		P
7.3.4	Thermal abuse (cells)		N/A
	Oven temperature (°C)..... :		—
	Results: No fire. No explosion		N/A
7.3.5	Crush (cells)		N/A
	The crushing force was released upon:		N/A
	- The maximum force of 13 kN ± 0.78 kN has been applied; or		N/A
	- An abrupt voltage drop of one-third of the original voltage has been obtained		N/A
	Results: No fire. No explosion .....		N/A
7.3.6	Over-charging of battery	Tested complied.	P
	The supply voltage which is:		P
	- 1.4 times the upper limit charging voltage presented in Table A.1 (but not to exceed 6.0 V) for single cell/cell block batteries or		N/A
	- 1.2 times the upper limit charging voltage resented in Table A.1 per cell for series connected multi-cell batteries, and		P
	- Sufficient to maintain a current of 2.0 It A throughout the duration of the test or until the supply voltage is reached		P
	Test was continued until the temperature of the outer casing:		P
	- Reached steady state conditions (less than 10 °C change in 30-minute period); or		N/A
	- Returned to ambient		P
	Results: No fire. No explosion .....	(See appended table 7.3.6)	P
7.3.7	Forced discharge (cells)		N/A
	If the discharge voltage reaches the negative value of upper limit charging voltage within the testing duration, the voltage is maintained at the negative value of the upper limit charging voltage by reducing the current for the remainder of the testing duration		N/A
	If the discharge voltage does not reach the negative value of upper limit charging voltage within the testing duration, the test is terminated at the end of the testing duration		N/A
	Results: No fire. No explosion .....		N/A

IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
7.3.8	Mechanical tests (batteries)		P
7.3.8.1	Vibration		P
	Results: No fire, no explosion, no rupture, no leakage or venting. .... :	(See appended table 7.3.8.1)	P
7.3.8.2	Mechanical shock		P
	Results: No leakage, no venting, no rupture, no explosion and no fire..... :	(See appended table 7.3.8.2)	P
7.3.9	Design evaluation – Forced internal short-circuit (cells)		N/A
	The cells complied with national requirement for..... :		—
	The pressing was stopped upon:		N/A
	- A voltage drop of 50 mV has been detected; or		N/A
	- The pressing force of 800 N (cylindrical cells) or 400 N (prismatic cells) has been reached		N/A
	Results: No fire..... :		N/A

<b>8</b>	<b>INFORMATION FOR SAFETY</b>		<b>P</b>
<b>8.1</b>	<b>General</b>		P
	Manufacturers of secondary cells ensure that information is provided about current, voltage and temperature limits of their products	Information for safety mentioned in manufacturer's specifications.	P
	Manufacturers of batteries ensure that equipment manufacturers and, in the case of direct sales, end-users are provided with information to minimize and mitigate hazards	Information for safety mentioned in manufacturer's specifications.	P
	Systems analyses performed by device manufacturers to ensure that a particular battery design prevents hazards from occurring during use of a product		P
	As appropriate, any information relating to hazard avoidance resulting from a system analysis provided to the end user		P
	Do not allow children to replace batteries without adult supervision		P
<b>8.2</b>	<b>Small cell and battery safety information</b>	Not small cell	N/A
	The following warning language is to be provided with the information packaged with the small cells and batteries or equipment using them:		N/A
	- Keep small cells and batteries which are considered swallowable out of the reach of children		N/A
	- Swallowing may lead to burns, perforation of soft tissue, and death. Severe burns can occur within 2 h of ingestion		N/A

IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
	- In case of ingestion of a cell or battery, seek medical assistance promptly		N/A
<b>9</b>	<b>MARKING</b>		<b>P</b>
<b>9.1</b>	<b>Cell marking</b>	The final product is battery.	N/A
	Cells marked as specified in IEC 61960, except coin cells		N/A
	Coin cells whose external surface area is too small to accommodate the markings on the cells show the designation and polarity		N/A
	By agreement between the cell manufacturer and the battery and/or end product manufacturer, component cells used in the manufacture of a battery need not be marked		N/A
<b>9.2</b>	<b>Battery marking</b>	See marking plate on page 4	P
	Batteries marked as specified in IEC 61960, except for coin batteries		P
	Coin batteries whose external surface area is too small to accommodate the markings on the batteries show the designation and polarity. Batteries also marked with an appropriate caution statement	Not coin cells.	N/A
	Terminals have clear polarity marking on the external surface of the battery		N/A
	Batteries with keyed external connectors designed for connection to specific end products need not be marked with polarity markings if the design of the external connector prevents reverse polarity connections		P
<b>9.3</b>	<b>Caution for ingestion of small cells and batteries</b>		N/A
	Coin cells and batteries identified as small batteries according to 8.2 include a caution statement regarding the hazards of ingestion in accordance with 8.2		N/A
	When small cells and batteries are intended for direct sale in consumer-replaceable applications, caution for ingestion given on the immediate package		N/A
<b>9.4</b>	<b>Other information</b>		P
	Storage and disposal instructions	Information for disposal instructions given in manufacturer's specifications.	P
	Recommended charging instructions	Information for recommended charging instructions given in manufacturer's specifications.	P

IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
<b>10</b>	<b>PACKAGING AND TRANSPORT</b>		<b>P</b>
	Packaging for coin cells not small enough to fit within the limits of the ingestion gauge of Figure 3	Not coin cell	N/A
	The materials and packaging design are chosen so as to prevent the development of unintentional electrical conduction, corrosion of the terminals and ingress of environmental contaminants		P

<b>ANNEX A</b>	<b>CHARGING AND DISCHARGING RANGE OF SECONDARY LITHIUM ION CELLS FOR SAFE USE</b>		<b>P</b>
<b>A.1</b>	<b>General</b>		P
<b>A.2</b>	<b>Safety of lithium ion secondary battery</b>	Complied.	P
<b>A.3</b>	<b>Consideration on charging voltage</b>	Complied.	P
A.3.1	General		P
A.3.2	Upper limit charging voltage	4.2V	P
A.3.2.1	General		P
A.3.2.2	Explanation of safety viewpoint		P
A.3.2.3	Safety requirements, when different upper limit charging voltage is applied		P
<b>A.4</b>	<b>Consideration of temperature and charging current</b>		P
A.4.1	General		P
A.4.2	Recommended temperature range		P
A.4.2.1	General		P
A.4.2.2	Safety consideration when a different recommended temperature range is applied	Charging temperature declared by client is: 0-45°C	P
A.4.3	High temperature range	Charging high temperature declared by client is: 45°C	N/A
A.4.3.1	General		N/A
A.4.3.2	Explanation of safety viewpoint		N/A
A.4.3.3	Safety considerations when specifying charging conditions in the high temperature range		N/A
A.4.3.4	Safety considerations when specifying a new upper limit in the high temperature range		N/A
A.4.4	Low temperature range	Low charging temperature declared by manufacturer is 0 °C	P
A.4.4.1	General		P
A.4.4.2	Explanation of safety viewpoint		P
A.4.4.3	Safety considerations, when specifying charging conditions in the low temperature range		P



IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
A.4.4.4	Safety considerations when specifying a new lower limit in the low temperature range		P
A.4.5	Scope of the application of charging current		P
A.4.6	Consideration of discharge		P
A.4.6.1	General		P
A.4.6.2	Final discharge voltage and explanation of safety viewpoint		P
A.4.6.3	Discharge current and temperature range		P
A.4.6.4	Scope of application of the discharging current		P
<b>A.5</b>	<b>Sample preparation</b>		N/A
A.5.1	General		N/A
A.5.2	Insertion procedure for nickel particle to generate internal short		N/A
A.5.3	Disassembly of charged cell		N/A
A.5.4	Shape of nickel particle		N/A
A.5.5	Insertion of nickel particle in cylindrical cell		N/A
A.5.5.1	Insertion of nickel particle in winding core		N/A
A.5.5.2	Marking the position of the nickel particle on both ends of the winding core of the separator		N/A
A.5.6	Insertion of nickel particle in prismatic cell		N/A
<b>A.6</b>	<b>Experimental procedure of the forced internal short-circuit test</b>		N/A
A.6.1	Material and tools for preparation of nickel particle		N/A
A.6.2	Example of a nickel particle preparation procedure		N/A
A.6.3	Positioning (or placement) of a nickel particle		N/A
A.6.4	Damaged separator precaution		N/A
A.6.5	Caution for rewinding separator and electrode		N/A
A.6.6	Insulation film for preventing short-circuit		N/A
A.6.7	Caution when disassembling a cell		N/A
A.6.8	Protective equipment for safety		N/A
A.6.9	Caution in the case of fire during disassembling		N/A
A.6.10	Caution for the disassembling process and pressing the electrode core		N/A
A.6.11	Recommended specifications for the pressing device		N/A
<b>ANNEX B</b>	<b>RECOMMENDATIONS TO EQUIPMENT MANUFACTURERS AND BATTERY ASSEMBLERS</b>		<b>N/A</b>

IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict
<b>ANNEX C</b>	<b>RECOMMENDATIONS TO THE END-USERS</b>		<b>N/A</b>
<b>ANNEX D</b>	<b>MEASUREMENT OF THE INTERNAL AC RESISTANCE FOR COIN CELLS</b>		<b>N/A</b>
<b>D.1</b>	<b>General</b>		N/A
<b>D.2</b>	<b>Method</b>		N/A
	A sample size of three coin cells is required for this measurement.....:		N/A
	Coin cells with an internal resistance of less than or equal to 3 $\Omega$ are subjected to the testing according to Clause 6 and Table 1		N/A
	Coin cells with an internal resistance greater than 3 $\Omega$ require no further testing		N/A
<b>ANNEX E</b>	<b>PACKAGING AND TRANSPORT</b>		<b>N/A</b>
<b>ANNEX F</b>	<b>COMPONENT STANDARDS REFERENCES</b>		<b>N/A</b>

IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict

TABLE: Critical components information (BL0950CAA652S1P****)					P
Object / part No.	Manufacturer / trademark	Type / model	Technical data	Standard <sup>2)</sup>	Mark(s) of conformity <sup>1)</sup>
Cell	GlobTek, Inc.	IMR14650	3,7 V 950 mAh 3,52 Wh	IEC 62133-2:2017	Certificate No: JPTUV-120479
PCB	SHENZHEN JIA LI CHUANG TECHNOLOGY DEVELOPMENT CO LTD	JLC-1	min. V-0, 130 °C	UL 796	Tested with battery UL E78017
Alternative	Interchangeable	Interchangeable	min. V-0, 130 °C	UL 796	UL approved
IC (U1)	HYCON TECHNOLOGY	HY2120	4,25 V	IEC 62133-2:2017	Tested with battery
Mosfet (U2)	NCEPOWER	NCE2010E	7 A 20 V	IEC 62133-2:2017	Tested with battery
IC (U3)	HYCON TECHNOLOGY	HY4231	High Temperature Operating Life: 125 °C, 1000 hrs.	IEC 62133-2:2017	Tested with battery
Supplementary information:					
1) Provided evidence ensures the agreed level of compliance. See OD-CB2039.					
2) License available upon request.					

TABLE: Critical components information (BL0950C146502S1P****)					P
Object / part No.	Manufacturer / trademark	Type / model	Technical data	Standard <sup>2)</sup>	Mark(s) of conformity <sup>1)</sup>
Cell	GlobTek, Inc.	IMR14650	3,7 V 950 mAh 3,52 Wh	IEC 62133-2:2017	Certificate No: JPTUV-120479
PCB	SHENZHEN JIA LI CHUANG TECHNOLOGY DEVELOPMENT CO LTD	JLC-1	min. V-0, 130 °C	UL 796	Tested with battery UL E78017
Alternative	Interchangeable	Interchangeable	min. V-0, 130°C	UL 796	UL approved
IC (U1)	HYCON TECHNOLOGY	HY2120	4,25 V	IEC 62133-2:2017	Tested with battery
Mosfet (U2)	NCEPOWER	NCE2010E	7 A 20 V	IEC 62133-2:2017	Tested with battery
Wire (Optional)	Interchangeable	Interchangeable	Min. 24 AWG, min.300 V, min. 80 °C	UL 758	UL approved
Connector (Optional)	JST	PHR-3	Min.V-2	IEC 62133-2:2017	Tested with battery UL E60389

IEC 62133-2					
Clause	Requirement + Test			Result - Remark	Verdict
Connector Alternativ	Interchangeable	Interchangeable	Min.V-2	--	UL approved
Supplementary information: <sup>1)</sup> Provided evidence ensures the agreed level of compliance. See OD-CB2039. <sup>2)</sup> License available upon request.					

IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict

7.2.1	TABLE: Continuous charging at constant voltage (cells)				N/A
Sample no.	Recommended charging voltage V <sub>c</sub> (Vdc)	Recommended charging current I <sub>rec</sub> (A)	OCV before test (Vdc)	Results	
<b>Supplementary information:</b>					
- No fire or explosion					
- No leakage					
- Others (please explain)					

7.3.1	TABLE: External short-circuit (cell)					N/A
Sample no.	Ambient T (°C)	OCV before test (Vdc)	Resistance of circuit (mΩ)	Maximum case temperature rise ΔT (K)	Results	
<b>Samples charged at charging temperature upper limit °C</b>						
<b>Samples charged at charging temperature lower limit °C</b>						
<b>Supplementary information:</b>						
- No fire or explosion						
- Others (please explain)						

IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict

7.3.2	TABLE: External short-circuit					P
Sample no.	Ambient T (°C)	OCV before test (Vdc)	Resistance of circuit (mΩ)	Maximum case temperature rises ΔT (K)	Component single fault condition	Results
BL0950CAA65 2S1PFCT (#004)	21,0	8,336	80	2,2	--	No fire or explosion
BL0950CAA65 2S1PFCT (#005)	21,0	8,351	80	3,1	--	No fire or explosion
BL0950CAA65 2S1PFCT (#006)	21,0	8,314	80	2,5	--	No fire or explosion
BL0950CAA65 2S1PFCT (#007)	21,0	8,325	80	2,0	--	No fire or explosion
BL0950CAA65 2S1PFCT (#008)	21,0	8,312	80	23,2	U2 SC	No fire or explosion
BL0950C14650 2S1PGKT (#023)	21,2	8,344	80	26,2	U2 SC	No fire or explosion
BL0950C14650 2S1PGKT (#024)	21,2	8,343	80	2,2	--	No fire or explosion
BL0950C14650 2S1PGKT (#025)	21,2	8,342	80	2,9	--	No fire or explosion
BL0950C14650 2S1PGKT (#026)	21,2	8,350	80	2,5	--	No fire or explosion
BL0950C14650 2S1PGKT (#027)	21,2	8,352	80	1,2	--	No fire or explosion
BL0950C146502 S1PGKTM (#033)	21,0	8,321	80	2,2	U2 SC	No fire or explosion
BL0950C146502 S1PGKTM (#034)	21,0	8,310	80	1,4	--	No fire or explosion
BL0950C146502 S1PGKTM (#035)	21,0	8,352	80	2,7	--	No fire or explosion
BL0950C146502 S1PGKTM (#036)	21,0	8,350	80	1,7	--	No fire or explosion
BL0950C146502 S1PGKTM (#037)	21,0	8,341	80	1,5	--	No fire or explosion
<b>Supplementary information:</b> 24 hours elapsed.						
- No fire or explosion						
- Others (please explain)						
- S-C=Short Circuit						

IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict

7.3.5	TABLE: Crush (cells)				N/A
Sample no.	OCV before test (Vdc)	OCV at removal of crushing force (Vdc)	Maximum force applied to the cell during crush (kN)	Results	
<b>Samples charged at charging temperature upper limit °C</b>					
<b>Samples charged at charging temperature lower limit °C</b>					
<b>Supplementary information:</b>					
- No fire or explosion					
- Others (please explain)					

7.3.6	TABLE: Over-charging of battery				P
Sample no.	OCV before charging (Vdc)	Total charging time (minute)	Maximum outer case temperature (°C)	Results	
Constant charging current (A) .....		1,9		—	
Supply voltage (Vdc) .....		10,08		—	
BL0950CAA652S 1PFCT (#012)	6,688	40	29,2	No fire or explosion	
BL0950CAA652S 1PFCT (#013)	6,749	40	28,5	No fire or explosion	
BL0950CAA652S 1PFCT (#014)	6,737	40	31,4	No fire or explosion	
BL0950CAA652S 1PFCT (#015)	6,695	40	29,6	No fire or explosion	
BL0950CAA652S 1PFCT (#016)	6,937	40	31,0	No fire or explosion	
BL0950C14650 2S1PGKT (#028)	6,756	40	29,0	No fire or explosion	

IEC 62133-2				
Clause	Requirement + Test		Result - Remark	Verdict
BL0950C14650 2S1PGKT (#029)	6,767	40	29,1	No fire or explosion
BL0950C14650 2S1PGKT (#030)	6,746	40	28,9	No fire or explosion
BL0950C14650 2S1PGKT (#031)	6,800	40	29,1	No fire or explosion
BL0950C14650 2S1PGKT (#032)	6,804	40	30,2	No fire or explosion
BL0950C146502S 1PGKTM (#038)	6,731	40	30,6	No fire or explosion
BL0950C146502S 1PGKTM (#039)	6.709	40	30,2	No fire or explosion
BL0950C146502S 1PGKTM (#040)	6,722	40	27,9	No fire or explosion
BL0950C146502S 1PGKTM (#041)	6,808	40	29,3	No fire or explosion
BL0950C146502S 1PGKTM (#042)	6,758	40	28,3	No fire or explosion
<b>Supplementary information:</b>				
- No fire or explosion				
- Others (please explain)				

7.3.7	TABLE: Forced discharge (cells)			N/A
Sample no.	OCV before application of reverse charge (Vdc)	Measured reverse charge $I_t$ (A)	Lower limit discharge voltage (Vdc)	Results
<b>Supplementary information:</b>				
- No fire or explosion				
- Others (please explain)				



IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict

7.3.8.1	TABLE: Vibration					P
Sample no.	OCV before test (Vdc)	OCV after test (Vdc)	Mass before test (g)	Mass after test (g)	Results	
BL0950CAA652S 1PFCT (#017)	8,332	8,331	60,2	60,2	No fire or explosion. No rupture or leakage. No venting.	
BL0950CAA652S 1PFCT (#018)	8,354	8,353	60,3	60,3	No fire or explosion. No rupture or leakage. No venting.	
BL0950CAA652S 1PFCT (#019)	8,342	8,341	60,3	60,3	No fire or explosion. No rupture or leakage. No venting.	
<b>Supplementary information:</b>						
<ul style="list-style-type: none"> <li>- No fire or explosion</li> <li>- No rupture</li> <li>- No leakage</li> <li>- No venting</li> <li>- Others (please explain)</li> </ul>						

7.3.8.2	TABLE: Mechanical shock					P
Sample no.	OCV before test (Vdc)	OCV after test (Vdc)	Mass before test (g)	Mass after test (g)	Results	
BL0950CAA652S 1PFCT (#020)	8,342	8,342	60,4	60,4	No fire or explosion. No rupture or leakage. No venting.	
BL0950CAA652S 1PFCT (#021)	8,337	8,337	60,7	60,7	No fire or explosion. No rupture or leakage. No venting.	
BL0950CAA652S 1PFCT (#022)	8,345	8,345	61,2	61,2	No fire or explosion. No rupture or leakage. No venting.	

IEC 62133-2			
Clause	Requirement + Test	Result - Remark	Verdict

**Supplementary information:**

- No fire or explosion
- No rupture
- No leakage
- No venting
- Others (please explain)

7.3.9	TABLE: Forced internal short circuit (cells)					N/A
Sample no.	Chamber ambient T (°C)	OCV before test (Vdc)	Particle location <sup>1)</sup>	Maximum applied pressure (N)	Results	
<b>Samples charged at charging temperature upper limit °C</b>						
<b>Samples charged at charging temperature lower limit °C</b>						

**Supplementary information:**

<sup>1)</sup> Identify one of the following:

- 1: Nickel particle inserted between positive and negative (active material) coated area.
  - 2: Nickel particle inserted between positive aluminium foil and negative active material coated area.
- No fire or explosion
  - Others (please explain)

D.2	TABLE: Internal AC resistance for coin cells				N/A
Sample no.	Ambient T (°C)	Store time (h)	Resistance Rac (Ω)	Results <sup>1)</sup>	

**Supplementary information:**

<sup>1)</sup> Coin cells with internal resistance less than or equal to 3 Ω, see test result on corresponding tables

## Attachment I:

IEC62133_2A ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
ATTACHMENT TO TEST REPORT IEC 62133-2 (Republic of Korea) NATIONAL DIFFERENCES (Secondary cells and batteries containing alkaline or other non-acid electrolytes - Safety requirements for portable sealed secondary lithium cells, and for batteries made from them, for use in portable applications - Part 2: Lithium systems)			
Differences according to..... : National standard KC62133-2(2020-07)			
TRF template used:..... : IECEE OD-2020-F3, Ed. 1.1			
Attachment Form No..... : KR_ND_IEC62133_2A			
Attachment Originator..... : KTR			
Master Attachment..... : Dated 2020-09-25			
Copyright © 2020 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.			
	National Differences		P
7.3.6	Over-charging of battery		P
(Revision)	<p><b><i>[Add the bolded text]</i></b></p> <p>b) Test</p> <p>The test shall be carried out in an ambient temperature of 20 °C ± 5 °C. Each test battery shall be discharged at a constant current of 0,2 It A, to a final discharge voltage specified by the manufacturer. Sample batteries shall then be charged at a constant current of 2,0 It A, using a supply voltage which is:</p> <ul style="list-style-type: none"> <li>• 1,4 times the upper limit charging voltage presented in Table A.1 (but not to exceed 6,0 V) for single cell/cell block batteries or</li> <li>• 1,2 times the upper limit charging voltage presented in Table A.1 per cell for series connected multi-cell batteries, and</li> <li>• sufficient to maintain a current of 2,0 It A throughout the duration of the test or until the supply voltage is reached.</li> </ul> <p><b><u>• In case the charging voltage specified by the manufacturer is higher than the overcharge test voltage, the maximum charging voltage specified by manufacturer should be applied with 2.0 ItA, (e.g., quick charging power bank, etc.)</u></b></p>	<p>The charging voltage specified by the manufacturer is lower than the overcharge test voltage.</p>	P

IEC62133_2A ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
	<p><b>[Replace to the following statement]</b></p> <p>c) Acceptance criteria Overcharging exceeding to the limits specified by the manufacturer should not result in fire or explosion.</p>		P
<b>Annex G</b>	<b>Definition for shape and materials of outer case for cell</b>		—
(Addition)	<p>G.1 General Annex G provides definitions for shape and materials of outer case for cell</p> <p>G.2 Shape of outer case for cell G 2.1 Cylindrical cell Cell with a cylindrical shape in which the overall height is equal to or greater than diameter.</p> <p>G 2.2 Prismatic cell Cell having the shape of a parallelepiped whose faces are rectangular</p> <p>G.3 Materials of outer case for cell G.3.1 Soft case Non-metallic outer case or container for cell</p> <p>G.3.2 Hard case Metallic outer case or container for cell.</p>	<p>(Shape of outer cases)</p> <p><input checked="" type="checkbox"/> Cylindrical <input type="checkbox"/> Prismatic</p> <p>(Materials of outer cases)</p> <p><input checked="" type="checkbox"/> Hard <input type="checkbox"/> Soft</p>	—
<b>Annex H</b>	<b>Calculation method of the volumetric energy density for cell</b>		—
(Addition)	<p>Annex H provide a calculation method of the volumetric energy density for cell in use of smart phone, tablet, notebook.</p> <p>H.1 General Unless otherwise stated in the Annex E, the dimensions for calculation are based on these for cell before shipment and the volumetric energy density shall be calculated with a maximum values specified by manufacturer. If the specification for cell can't be provided a dimension for calculation, the manufacturer's other documentation shall be provided to demonstrate compliance for its calculation.</p>	356,36 Wh / L	—

IEC62133_2A ATTACHMENT			
Clause	Requirement + Test	Result - Remark	Verdict
	<p><b>H.2 Calculation Method</b></p> <p>L : Length (max.) of cell (including terrace)  W : Width (max.) of cell  T : Thickness (max.) when shipping charge  (For reference, Please  Exclude the dimension of any tape that  is attached to cell)</p> $\text{Volumetric energy density (Wh/L)} = \frac{\text{Nominal voltage (V)} \times \text{Rated capacity (Ah)}}{\text{Length (L)} \times \text{Width (W)} \times \text{Thickness (T)}}$ <p><b>[H.1 – Prismatic cell using soft case]</b></p> <p>L : Length (max.) of cell  W : Width (max.) of cell  T : Thickness when shipping charge  (For reference, Please  Exclude the dimension of any tape that  is attached to cell)</p> $\text{Volumetric energy density (Wh/L)} = \frac{\text{Nominal voltage (V)} \times \text{Rated capacity (Ah)}}{\text{Length (L)} \times \text{Width (W)} \times \text{Thickness (T)}}$ <p><b>[H.2 – Prismatic cell using hard case]</b></p> <p>D : Diameter (max.) of cell  L : Length (max.) of cell  (According to shape of cell at shipping,  The dimension of tube for cell may be included  in overall dimension of cell )</p> $\text{Volumetric energy density (Wh/L)} = \frac{\text{Nominal voltage (V)} \times \text{Rated capacity (Ah)}}{3.14159 \times \frac{\text{Diameter (D)}^2}{4} \times \text{Length(L)}}$ <p><b>[H.3 – Cylindrical cell using hard case]</b></p>		

Attachment I: Photos

Photo 1.  
Battery view for BL0950CAA652S1PFCT



Photo 2.  
Battery view for BL0950CAA652S1PFCT



Photo 3.

Battery view for BL0950CAA652S1PFCT



Photo 4.

Battery internal view for BL0950CAA652S1PFCT



Photo 5.

Battery internal view for BL0950CAA652S1PFCT




Photo 6.

Battery internal view for BL0950CAA652S1PFCT





Photo 7  
PCB view for BL0950CAA652S1PFCT




Photo 8.  
PCB view for BL0950CAA652S1PFCT




Photo 9

Cell view for BL0950CAA652S1PFCT



Photo 10.

Battery view for BL0950C146502S1PGKT



Photo 11

Battery internal view for BL0950C146502S1PGKT




Photo 12

Battery internal view for BL0950C146502S1PGKT




Photo 13

Battery internal view for BL0950C146502S1PGKT




Photo 14

Battery view for BL0950C146502S1PGKTM




Photo 15

Battery view for BL0950C146502S1PGKTM



Photo 16

Battery internal view for BL0950C146502S1PGKTM



Photo 17

Battery internal view for BL0950C146502S1PGKTM



Photo 18

PCB view for BL0950C146502S1PGKTM




Photo 19

PCB view for BL0950C146502S1PGKTM




Photo 20

Cell view for BL0950C146502S1PGKTM



----- End of Report -----