

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT  
(IECEE) CB SCHEME

## CB TEST CERTIFICATE

Product

Direct Plug-in Power Supply

Name and address of the applicant

GlobTek, Inc.  
186 Veterans Drive Northvale, NJ 07647, USA

Name and address of the manufacturer

GlobTek, Inc.  
186 Veterans Drive Northvale, NJ 07647, USA

Name and address of the factory

See page 2

*Note: When more than one factory, please report on page 2*

Ratings and principal characteristics

☒ Additional Information on page 2

See page 2

Trademark (if any)



GlobTek, Inc.

Customer's Testing Facility (CTF) Stage used

/

Model / Type Ref.

GT-41052-WWVV-X.X

Additional information (if necessary may also be reported on page 2)

Unit also complies with EN 60950-1:2006 + A1:2010 + A2:2013 + A11:2009 + A12:2011

A sample of the product was tested and found to be in conformity with

☒ Additional Information on page 2

IEC 60950-1:2005 + A1:2009 + A2:2013

As shown in the Test Report Ref. No. which forms part of this Certificate

T223-0247/19, dated 2019-06-11


This CB Test Certificate is issued by the National Certification Body

SIQ Ljubljana, Tržaška cesta 2, SI-1000 Ljubljana, Slovenia  
T +386 1 4778 100, F +386 1 4778 444, info@siq.si, www.siq.si

SIQ Ljubljana is accredited by Slovenian Accreditation with accreditation number CP-001 in the field of certification of products, processes and services.

Date: 2019-06-11

Signature: Bojan Pečavar





**Name and address of the factories:**

1) GlobTek, Inc.  
186 Veterans DR, Northvale, NJ 07647, USA

2) GlobTek (Suzhou) Co., Ltd.  
Building 4, # 76, Jin Ling East Rd., Suzhou Park, Suzhou, Jiangsu 215021, P.R.China

**Model/Type reference:**

GT-41052-WWWV-X.X

WW is the standard output wattage, with a maximum value of "15"

VV is the standard rated output voltage designation, with a maximum value of "24"; which can be 05, 06, 07, 09, 12, 15, 18, 20, 24, 48.

-X.X denote the output voltage differentiator, subtracting X.X volts from standard output voltage VV in 0.01V increments, the actual output voltage rang is 5-48Vdc, blank is to indicate the no voltage different.

**Ratings and principal characteristics:**

Input: 100 – 240 Va.c.; 50 – 60 Hz; 0,6 A

Output: see table below

Model	Output Voltage(V)	Max.Output Current(A)	Max.Output Wattage(W)
GT-41052-WW05	5	2,60	13
GT-41052-WW06-X.X	5.01-6	2,60	15
GT-41052-WW07-X.X	6.01-7	2,49	15
GT-41052-WW09-X.X	7.01-9	2,13	15
GT-41052-WW12-X.X	9.01-12	1,66	15
GT-41052-WW15-X.X	12.01-15	1,24	15
GT-41052-WW18-X.X	15.01-18	0,99	15
GT-41052-WW20-X.X	18.01-20	0,83	15
GT-41052-WW24-X.X	20.01-24	0,74	15
GT-41052-WW48-X.X	24.01-48	0,62	15

**Additional information (if necessary)**

This CB test certificate substitutes previously issued CB test certificate No. SI-3450, dated 2012-09-04, due to update of test report.

Date: 2019-06-11

Signature: Bojan Pečavar

