



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO.: 2013010907615073

Valid from: Nov.15,2023

Valid until: Nov.06,2027

**NAME AND REGISTERED
ADDRESS OF THE APPLICANT**

GlobTek,Inc.
186 Veterans Dr Northvale, NJ 07647 / USA

**NAME AND REGISTERED
ADDRESS OF THE
MANUFACTURER**

GlobTek,Inc.
186 Veterans Dr Northvale, NJ 07647 / USA

**NAME AND LOCATION
OF THE FACTORY**

GlobTek (Suzhou) Co., Ltd
Building 4, No. 76 JinLing East Road,Suzhou Industrial Park, Suzhou, JiangSu, 215021, China.

PRODUCT MODEL(S)

power supply for business machine
See Appendix (Altitude up to 2000m)

**STANDARDS AND
TECHNICAL REQUIREMENTS**

GB 17625.1-2022 (Class A) ;GB 4943.1-2022;GB/T 9254.1-2021

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification(REFNO. CNCA-C09-01:2023)

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

Date of original issued: May.17,2013

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P

The certificate information is available through the QR code below or CNCA's website: www.cnca.gov.cn



SIGNATURE:

谢肇煦



CHINA QUALITY CERTIFICATION CENTRE





CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2013010907615073

page 1 of 2

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

GT-41052-WWVV-X.X SAD-PA/1201

WW is the standard output wattage, which can be 01 to 15 with interval of 1, maximum value of "15";

VV is the standard rated output voltage designation, with a maximum value of "48"; which can be 05, 06, 07, 09, 12, 15, 18, 20, 24, 48.

-X.X denote the output voltage differentiator, subtracting X.X volts from standard output voltage VV in 0.01V increments, the actual output voltage rang is 5-48Vdc, blank is to indicate the no voltage different.

Input: 100-240V ~ , 50-60Hz , 0.6A

Output: see below table

Model	Output Voltage	Max.Output Current	Max.Output Wattage
GT-41052-WW05	5.0 VDC	2.6 A	13W
GT-41052-WW06-X.X (-X.X=-0.1 ~ -0.9 or blank)	5.1-6.0 VDC	2.94 A	15W
GT-41052-WW07-X.X (-X.X=-0.1 ~ -0.9 or blank)	6.1-7.0 VDC	2.46 A	15W
GT-41052-WW09-X.X (-X.X=-0.1 ~ -1.9or blank)	7.1-9.0 VDC	2.11 A	15W
GT-41052-WW12-X.X (-X.X=-0.1 ~ -2.9 or blank)	9.1-12.0 VDC	1.65 A	15W
GT-41052-WW15-X.X (-X.X=-0.1 ~ -2.9 or blank)	12.1-15.0 VDC	1.24 A	15W
GT-41052-WW18-X.X (-X.X=-0.1 ~ -2.9 or blank)	15.1-18.0 VDC	0.99 A	15W
GT-41052-WW20-X.X (-X.X=-0.1 ~ -1.9 or blank)	18.1-20.0 VDC	0.83 A	15W
GT-41052-WW24-X.X	20.1-24.0 VDC	0.75 A	15W



CHINA QUALITY CERTIFICATION CENTRE



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2013010907615073

page 2 of 2

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

(-X.X=-0.1~-3.9 or blank)			
GT-41052-WW48-X.X (-X.X=-0.1~-23.9 or blank)	24.1-48.0 VDC	0.62 A	15W
SAD-PA/1201	12.0 VDC	1.25 A	15W



CHINA QUALITY CERTIFICATION CENTRE