

**KINGDOM OF SAUDI ARABIA
CONFORMITY ASSESSMENT PROGRAM**

Lic No: KSA L-103828

KSA CAP TYPE APPROVAL LICENCE

Product Category:	II-42 - POWER SUPPLIES AND BATTERY CHARGERS
Name and Address of the Applicant:	GlobTek, Inc 186 Veterans Dr Northvale NEW JERSEY 07647 UNITED STATES
Model / Type Reference:	See Appendix 1
Principal Characteristics:	See Appendix 1
Trade mark (if any):	GlobTek
Additional Information:	
Type approval evidence reference:	IEC 60950-1:2005



This Licence is issued by the CAP Registration and Licencing Centre under the authority of the Ministry of Commerce and Industry

Registration and Licensing Centre
Americas
04 August 2017

A handwritten signature in black ink, appearing to read "Maja Mellion", enclosed in a thin black rectangular border.

Maja Mellion
Registration and Licensing Manager

Date First Issued: 09 June 2014

Expiry Date: 04 August 2018

This Licence is for the exclusive use of Intertek's Client and is provided pursuant to the Licensing agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Licence. Only the Client is authorized to permit copying or distribution of this Licence and then only in its entirety. Any use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring compliance with the Licensing agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.

LIC. No. KSA L-103828
First issue date
09 June 2014

Model Type Reference	Product Description	Rating and Principal Characteristics	Standards	Type Approval Evidence Reference
GT*41078-*05-USB	ITE Power Supply. The 1st "*" part can be 'M' or '-' or 'H' for market identification and not related to safety. The 2nd "*" part denotes the rated output wattage designation, which can be "01" to "06", with interval of 1.		IEC 60950-1:2005	

LIC. No. KSA L-103828
First issue date
09 June 2014

Model Type Reference	Product Description	Rating and Principal Characteristics	Standards	Type Approval Evidence Reference
GT-41052-WWVV-X.XX**** ** Series	ITE Power Supply. WW is the standard output wattage, with a maximum value of "18", VV is the standard rated output voltage designation, with a maximum value of "24", which can be 05,09,12,15,18,24. -X.XX denote the output voltage differentiator, subtracting X.XX volts from standard output voltage VV in 0.01V increments, the actual output voltage range is 5-24V, blank is to indicate the no voltage different. Each*=0-9 or A-Z or ()[] or blank for mktg purpos		IEC 60950-1:2005	

LIC. No. KSA L-103828
First issue date
09 June 2014

Model Type Reference	Product Description	Rating and Principal Characteristics	Standards	Type Approval Evidence Reference
GT-41062-WWVV-X.XX**** ** Series	ITE Power Supply. WW is the standard output wattage, with a maximum value of "18", VV is the standard rated output voltage designation, with a maximum value of "24", which can be 05,09,12,15,18,24. -X.XX denote the output voltage differentiator, subtracting X.XX volts from standard output voltage VV in 0.01V increments, the actual output voltage range is 5-24V, blank is to indicate the no voltage different. Each*=0-9 or A-Z or ()[] or blank for mktg purpos		IEC 60950-1:2005	

LIC. No. KSA L-103828
First issue date
09 June 2014

Model Type Reference	Product Description	Rating and Principal Characteristics	Standards	Type Approval Evidence Reference
GT-41080-WWVV-X.XX**** ** Series	ITE Power Supply. WW is the standard output wattage, with a maximum value of "18", VV is the standard rated output voltage designation, with a maximum value of "24", which can be 05,09,12,15,18,24. -X.XX denote the output voltage differentiator, subtracting X.XX volts from standard output voltage VV in 0.01V increments, the actual output voltage range is 5-24V, blank is to indicate the no voltage different. Each*=0-9 or A-Z or ()[] or blank for mktg purpos		IEC 60950-1:2005	

LIC. No. KSA L-103828
First issue date
09 June 2014

Model Type Reference	Product Description	Rating and Principal Characteristics	Standards	Type Approval Evidence Reference
GT-41081-WWVV-X.XX**** ** Series	ITE Power Supply. WW is the standard output wattage, with a maximum value of "18", VV is the standard rated output voltage designation, with a maximum value of "24", which can be 05,09,12,15,18,24. -X.XX denote the output voltage differentiator, subtracting X.XX volts from standard output voltage VV in 0.01V increments, the actual output voltage range is 5-24V, blank is to indicate the no voltage different. Each*=0-9 or A-Z or ()[] or blank for mktg purpos		IEC 60950-1:2005	

LIC. No. KSA L-103828
First issue date
09 June 2014

Model Type Reference	Product Description	Rating and Principal Characteristics	Standards	Type Approval Evidence Reference
GT-41083-***-*. *-T2	NOTES CONTINUED.... The 3rd to 6th asterisks together denote the output voltage with a range of 12-18 volts.		IEC 60950-1:2005	
GT-41083-***-*. *-T2	ITE Power Supply. The first together with the second "*" denote the watt, which can be 01-41, with interval of 1. The third together with the fourth "*" denote the standard rated output voltage designation, which can be "12", "24", "48". "-*. *" denote the optional deviation, subtracted from standard output voltage, which can be "-0.1" to "-23.9" with interval of 0.1, or blank to indicate no voltage different.		IEC 60950-1:2005	

LIC. No. KSA L-103828
First issue date
09 June 2014

Model Type Reference	Product Description	Rating and Principal Characteristics	Standards	Type Approval Evidence Reference
GT-41130-WWVV-X.X-TZ	Power supply for business machine. WW-Watt. VV-X.X=Voltage. Z=2,3 or 3A		IEC 60950-1:2005	
GT-46180-WWVV-X.XX**** ** Series	ITE Power Supply. WW is the standard output wattage, with a maximum value of "18", VV is the standard rated output voltage designation, with a maximum value of "24", which can be 05,09,12,15,18,24. -X.XX denote the output voltage differentiator, subtracting X.XX volts from standard output voltage VV in 0.01V increments, the actual output voltage range is 5-24V, blank is to indicate the no voltage different. Each*=0-9 or A-Z or ()[] or blank for mktg purpos		IEC 60950-1:2005	