

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE	
Product	ITE/ICT Power Supply
Name and address of the applicant	GlobTek, Inc. 186 Veterans Drive Northvale NJ 7647 United States of America
Name and address of the manufacturer	GlobTek, Inc. 186 Veterans Drive Northvale NJ 7647 United States of America
Name and address of the factory	See next page(s)
Note: When more than one factory,please report on page 2	Additional Information on Page 2
Ratings and Principal characteristics	I/P: 0.6A, 100-240Vac, 50-60Hz or 50/60Hz
Trademark /Brand (If any)	output: 3-30 vdc, max 25 vv, max 3.00A
	GlobTek, Inc.
Customer's Testing Facility (CTF) Stage used	
Model/Type Ref	GTX41060ZWWVV-X.X
Additional information(If necessary may also be reported on Page 2)	Additional Information on Page 2
A sample of the product was tested and found to be in conformity with	IEC 62368-1:2018
As shown in the Test Report Ref. No. which forms part of this Certificate	REP004392
This CB Test Certificate is issued by the National Certification Body	
Nemko	

Philip Pedersen vei 11, NO-1366 Lysaker, Norway Date: 07-03-2023

Jiyea Gim

Signature: Jiyea Gim Certification department

Disclaimer: This document is controlled and has been released electronically. Only the version on the IECEE Website is the current document version



GlobTek, Inc. 186 Veterans Drive Northvale NJ 7647 United States of America GlobTek (Suzhou) Co., Ltd Building 4, No. 76, Jin Ling East Rd., Suzhou Industrial Park, Suzhou,JiangSu 215021 China

Additional Information (if necessary)

First X: can be 'M' or '-' for market identification and not related to safety. Z: can be - or CC, '-' = Constant Voltage Model, CC = Constant Current Model WW: rated output wattage, maximum 25 VV: rated output voltage, with a range of 3-30 -X.X is optional or blank, denotes the output voltage differentiator, subtracting or adding X.X volts from standard output voltage VV in 0.1V increments. VV-X.X together denotes a voltage range of 3-30Vdc. Maximum rated output current is 3.00A



Philip Pedersen vei 11, NO-1366 Lysaker, Norway Date: 07-03-2023

Jiyea Gim

Signature: Jiyea Gim Certification department

Disclaimer: This document is controlled and has been released electronically. Only the version on the IECEE Website is the current document version