

# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20150819-E341351  
**Report Reference** E341351-A70-UL  
**Issue Date** 2015-AUGUST-19

**Issued to:** GLOBTEK (HONG KONG) LTD  
UNIT 1402, BENSON TOWER  
74 HUNG TO RD  
KWUN TONG  
KOWLOON HONG KONG

**This is to certify that  
representative samples of**

POWER SUPPLIES, INFORMATION TECHNOLOGY  
EQUIPMENT INCLUDING ELECTRICAL BUSINESS  
EQUIPMENT

See Addendum Page for Models/Product

Have been investigated by UL in accordance with the  
Standard(s) indicated on this Certificate.

**Standard(s) for Safety:**

UL 60950-1, Information Technology Equipment - Safety -  
Part 1: General Requirements.  
CAN/CSA C22.2 No. 60950-1-07, Information Technology  
Equipment - Safety - Part 1: General Requirements.

**Additional Information:**

See the UL Online Certifications Directory at  
[www.ul.com/database](http://www.ul.com/database) for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's  
Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please  
contact a local UL Customer Service Representative at <http://ul.com/about/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20150819-E341351  
**Report Reference** E341351-A70-UL  
**Issue Date** 2015-AUGUST-19

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

ITE POWER SUPPLY -

GT-46180-WWVV-X.XX series, GT-41052-WWVV-X.XX [EL6] series, GT-41062-WWVV-X.XX [EL6] series, GT-41080-WWVV-X.XX [EL6] series and GT-41081-WWVV-X.XX [EL6] series

WW is the standard output wattage, with a maximum value of "18",

VV is the standard rated output voltage designation, with a maximum value of "24"; which can be 05,09,12,15,18,24.

-X.XX denote the output voltage differentiator, subtracting X.XX volts from standard output voltage VV in 0.01V increments, the actual output voltage range is 5-24V, blank is to indicate the no voltage different



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>

