CERTIFICATE OF COMPLIANCE

Certificate Number Report Reference Issue Date 20140213- E341351 E341351-A62-UL 2014-February-13

Issued to: GLOBTEK (HONG KONG) LTD UNIT 1402, BENSON TOWER 74 HUNG TO RD, KWUN TONG, KOWLOON HONG KONG.

This is to certify that representative samples of

At POWER SUPPLIES, INFORMATION TECHNOLOGY of EQUIPMENT INCLUDING ELECTRICAL BUSINESS EQUIPMENT. SEE ADDENDUM PAGE FOR MODELS

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety:UL 60950-1 and CSA C22.2 No. 60950-1-03- Information
Technology Equipment - Safety - Part 1: General
Requirements.Additional Information:See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Listing Mark for the US and Canada should be considered as being covered by UL's Listing and Follow-Up Service meeting the appropriate requirements for US

and Canada. The UL Listing Mark for the US and Canada generally includes: the UL in a circle symbol with "C" and "US" identifiers: ⁽¹⁾ the word "LISTED"; a control number (may be alphanumeric) assigned by UL;

and the product category name (product identifier) as indicated in the appropriate UL Directory.

Look for the UL Listing Mark on the product.

William R. Car.

William R. Carney, Director, North American Certification Programs UL LLC Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) o contact a local UL Customer Service Representative at <u>www.ul.com/contactus</u> (UL)

CERTIFICATE OF COMPLIANCE

Certificate Number Report Reference Issue Date 20140213- E341351 E341351-A62-UL 2014-February-13

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Switching Power Adapter- GT-41082-WWVV-X.X-TZ series: WW is the rated output wattage designation, with a maximum value of "18"; VV is the standard rated output voltage designation, with a maximum value of "15"; X.X designates the optional deviation, X.X should be VV minus the rated voltage, and it can be blank;

Z presents different inlets, where "3" presents C14, "3A" presents C6

William R. Carroy

William R. Carney, Director, North American Certification Programs UL LLC Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any ar contact a local UL Customer Service Representative at <u>www.ul.com/contactus</u> **(U)**