

CERTIFICATE OF COMPLIANCE

Certificate Number 20150819-E341351
Report Reference E341351-A69-UL
Issue Date 2015-AUGUST-19

Issued to: GLOBTEK (HONG KONG) LTD
UNIT 1402, BENSON TOWER
74 HUNG TO RD
KWUN TONG
KOWLOON HONG KONG

**This is to certify that
representative samples of**

POWER SUPPLIES, INFORMATION TECHNOLOGY
EQUIPMENT INCLUDING ELECTRICAL BUSINESS
EQUIPMENT

See Addendum Page for Models/Product

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:

UL 60950-1, Information Technology Equipment - Safety -
Part 1: General Requirements.
CAN/CSA C22.2 No. 60950-1-07, Information Technology
Equipment - Safety - Part 1: General Requirements.

Additional Information:

See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's
Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20150819-E341351
Report Reference E341351-A69-UL
Issue Date 2015-AUGUST-19

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

ITE Power Supply-

GT-46200-WVVV-X.XX-TZ, GT-41130-WVVV-X.XX-TZ [EL6]

WW is the standard output wattage, with a maximum value of "20",

VV is the standard rated output voltage designation, with a value of "05" and "06";

-X.XX denote the output voltage differentiator, subtracting X.XX volts from standard output voltage VV in 0.01V increments, the actual output voltage rang is 5-24V, blank is to indicate the no voltage different.

Z can be 3 or 3A, 3 means C14 inlet type, 3A means C6 inlet type



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>

