

## **CERTIFICATE**

No. P16220874





Order No. 305321

**Product ITE Power Supply** 

GlobTek, Inc. **Applicant** 

186 Veterans Drive Northvale, NJ 07647

**USA** 

GlobTek, Inc. Manufacturer

> 186 Veterans Drive Northvale, NJ 07647

USA

**Factory** See page 2

Input: 0.8A 100-240Vac 50-60Hz Ratings

Trade mark

Validity

GlobTek, Inc

GT-41130-20VV-X.X-Wy Model / Type Ref.

Principal characteristics Cl. II. Output: 2.0-1.0A, 10-24Vdc, max. 24W.

A sample of the product was tested and found to be in conformity with

EN 60950-1:2006;A11;A1;A12;A2 OFF

This certificate documents conformity with the standards shown, and also applies as license for use of Nemkos name and certification mark. The certificate and license is valid as long as the applicable conditions are complied with, and provided that any changes to the product are notified to Nemko for acceptance prior to implementation.

New standards or amendments to the standards may imply that the product design must be

updated and/or that re-testing and re-certification is necessary.

Additional information See page 2

> Compliance with requirements regarding electromagnetic compatibility (EMC) is based on a self declaration from the manufacturer/representative according to the European EMC Directive.

Additional model(s) No additional models

Date of issue 24-03-2016

Sweet Yuan

Certification Department



## **CERTIFICATE**

No. P16220874





Order No. 305321 Page 2 of 2

**Factories** 

GlobTek, Inc. 186 Veterans Drive Northvale, NJ 07647 USA

GlobTek (Suzhou) Co., Ltd Building 4, No. 76, Jin Ling East Rd., Suzhou Industrial Park, Suzhou, JiangSu 215021 China

Additional information

In model name: The "VV" denotes the output voltage, which can be 10-24Vdc. The X.X denotes the optional deviation, subtracted from standard output voltage in 0.1 volt increments or blank to indicate the no voltage different. The "y" denotes the type of plug, which can be "2E" (denote Europe plug), "2U" (denote British plug), "2A" (denote Australia plug), "2C" (denote Chinese plug), blank (denote American/Japan/Taiwan plug). Max. 20W for output voltage (10-12V, excluded 12V), Max. 24W for output voltage (12-24V, included 12V).

Date of issue 24-03-2016

Sweet Yuan

Certification Department

Nemko AS