

CERTIFICATE FOR CANNOT BE USED IN ISOLATION CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO.: 2015010907758510

NAME AND ADDRESS OF THE APPLICANT

GlobTek,Inc.

186 Veterans Dr. Northvale, NJ 07647, USA

NAME AND ADDRESS OF THE MANUFACTURER

GlobTek,Inc.

186 Veterans Dr. Northvale, NJ 07647, USA

NAME AND LOCATION OF THE FACTORY

GlobTek (Suzhou) Co., Ltd

Building 4, No. 76 JinLing East Road, Suzhou Industrial Park, Suzhou, JiangSu, 215021, China.

PRODUCT NAME, MODEL AND SPECIFICATION

Power supply for business machine See appendix(Sale without cord set, Altitude up to 2000m)

STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS

GB 17625.1-2022 (Class A) ;GB 4943.1-2022;GB/T 9254.1-2021

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification(REFNO. CNCA-C09-01:2023).

Valid from: Mar.07,2024 Valid until: Dec.11,2024

Date of original issued: Mar.05,2015

The certificate information and validity could be checked by scanning the QR code below or logging in to the website of the issuing authority, or on the website of the CNCA (www.cnca.gov.cn).

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P



SIGNATURE: 为学文、中国质量认证中心

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.



This translated document does not have legal validity and cannot be used in isolation



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO.: 2015010907758510

Appendix: Page 1 of 1

GT-41132-WWVV-X.X-TZ (WW denotes rated output power, which can be 01 to 65, and the step is 1; VV denotes the rated output voltage, which can be 12 or 24;-X.X denotes the optional voltage deviation, subtracted from standard rated output voltage, which can be -0.1 to -11.9, or blank to indicate the no voltage difference, the step is 0.1V; VV-X.X together denotes output voltage; Z can be 3 or 3A, represents different input sockets.)

Input: $100-240V \sim$, 50-60Hz, 1.5A;

Output: see below

Model	DC Output Voltage	Max. Output current	Max. Output power
GT-41132-WW12-TZ	12Vdc	5A	60W
GT-41132-WW24-X.X -TZ (-X.X=-11.9- 5.1)	12.1V-18.9Vdc	4.96A	60W
GT-41132-WW24-X,X -TZ (-X.X=-5.0-0.1 or blank)	19V-24Vdc	3.42A	65W

This page is attached to the certificate and should be used at the same time as the certificate page.



CHINA QUALITY CERTIFICATION CENTRE CO., LTD.