

Certificate



Intertek

for European Product Safety

Reference No. 1710921

ITE Power supply

Type designation GT*961200P****, GT*96900P****, GT*41133-*****

Certificate holder **GlobTek, Inc.**
186 Veterans Dr. Northvale NJ 07647,
USA

The product complies with the standard(s) EN 60950-1: 2006+A11:2009+A1:2010+A12:2011+A2:2013

Date of expiry 05 May 2022

Additional information in Appendix.

Certification Body Intertek Semko AB, Product Certification *Place* Shanghai

Signed

Gary Hu

Date 05 May 2017
Page 1 of 3


This certificate is issued in accordance with the terms and conditions set out in the Appendix.



Intertek Appendix

Reference No. 1710921

Technical data

Type designation	GT*961200P****, GT*96900P****, GT*41133-*****
Input	100-240V~, 50-60Hz, 1.5A
Output	12-54VDC, Max. 10A, Max 120W
BRAND name:	
Product information	Details see attachment

Attachment:

GT*961200P****, GT*96900P**** and GT*41133-*****.

The 1st "*" part can be 'M' or 'L' or 'H' for market identification and not related to safety.

When model = GT*41133-*****

The 2nd "*" denotes the rated output wattage designation, which can be "01" to "90", with interval of 1.

The 3rd "*" denotes the standard rated output voltage designation, which can be "16", "24", "35" and "48".

The 4th "*" part is optional, which can be "-0.1" to "-12.9" with interval of 0.1 to denote voltage deviation or blank to indicate no voltage different.

The 3rd "*" and 4th "*" together denote the output voltage, with a range of 12 - 48 volts

The 5th "*"

--T2 means desktop class II with C8 AC inlet

--T3A means desktop class I with C6 AC inlet

--F means Open Frame class I

--FW means Open Frame class II

The last * denote any six character = 0-9 or A-Z or () [] or - or blank for marketing purposes.

When model = GT*961200P** and GT*96900P******

The 2nd "*" denotes the rated output wattage designation, which can be "-01" to "-120", with interval of 1 and "-" can be omitted.

The 3rd "*" denote the standard rated output voltage designation, which can be "12" to "54" or "12.0" to "54.0" in 0.1V increments

The 4th "*"

--T2 means desktop class II with C8 AC inlet

--T2A means desktop class II with C18 AC inlet

--T3 means desktop class I with C14 AC inlet

--T3TAB means desktop class I with C14 AC inlet and housing with a tab.

--T3A means desktop class I with C6 AC inlet

The last * denote any six character = 0-9 or A-Z or () [] or - or blank for marketing purposes.

This Certificate is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this certificate. Only the Client is authorized to permit copying or distribution of this certificate and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.



Reference No. 1710921

Ratings:

When model = GT*41133-*****, Input: 100-240V~, 50-60Hz, 1.5A; Output: 12-48Vdc, Max. 7.5A, Max. 90W

When model = GT*96900P****, Input: 100-240V~, 50-60Hz, 1.5A; Output: 12-54Vdc, Max. 7.5A, Max. 90W

When model = GT*961200P****, Input: 100-240V~, 50-60Hz, 1.5A; Output: 12-54Vdc, Max. 10A, Max. 120W

Manufacturing site(s)

GlobTek (Suzhou) Co., Ltd
Building 4, No. 76, Jin Ling East Rd., Suzhou Industrial Park, Suzhou,
JiangSu 215121,
P.R.China

If the product is to be marketed in different European countries, it must be provided with a certified plug appropriate for each country.

Safety related parts of the user instructions shall be written in a language acceptable to the country where the product is to be used.

Certification Body

Intertek Semko AB, Product Certification

Place Shanghai

Signed



Gary Hu

Date 05 May 2017

This Certificate is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this certificate. Only the Client is authorized to permit copying or distribution of this certificate and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.