CERTIFICATE OF COMPLIANCE

20131223-E341351 Certificate Number E341351-A33-UL Report Reference 2013-DECEMBER-23 **Issue Date**

> GLOBTEK (HONG KONG) LTD Issued to:

> > **UNIT 1402, BENSON TOWER**

74 HUNG TO RD **KWUN TONG**

KOWLOON HONG KONG

This is to certify that representative samples of POWER SUPPLIES, INFORMATION TECHNOLOGY EQUIPMENT INCLUDING ELECTRICAL BUSINESS

EQUIPMENT

See next page

Have been investigated by UL in accordance with the

Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 60950-1- Information Technology Equipment - Safety -

Part 1: General Requirements)

CSA C22.2 No. 60950-1-07- Information Technology Equipment - Safety - Part 1: General Requirements

Additional Information: See the UL Online Certifications Directory at

www.ul.com/database for additional information

Only those products bearing the UL Listing Mark for the US and Canada should be considered as being covered by UL's Listing and Follow-Up Service meeting the appropriate requirements for US and Canada.

The UL Listing Mark for the US and Canada generally includes: the UL in a circle symbol with "C" and "US" identifiers: ^c(U) us the word "LISTED"; a control number (may be alphanumeric) assigned by UL; and the product category name (product identifier) as indicated in the appropriate UL Directory.

Look for the UL Listing Mark on the product.

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) contact a local UL Customer Service Representative at www.ul.com/contactus



CERTIFICATE OF COMPLIANCE

Certificate Number 20
Report Reference E3
Issue Date 20

20131223-E341351 E341351-A33-UL 2013-DECEMBER-23

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

SWITCHING POWER ADAPTER

GT-41133-WWVV-X.X-AB

WW" is the rated output wattage designation, with a maximum value of 90.

"VV" is the standard rated output voltage designation, with a maximum value of 48V.

"-X.X" is optional or blank and denotes the output voltage differentiator, subtracting or adding X.X volts from standard output voltage VV in 0.1V increments.

"VV-X.X" together denotes a voltage range of "12-48" Vdc.

A=T; B= 2 or 3 or 3A,"2" means class II, 3 or 3A means Class I, where"3" presents C14 type inlet, "3A" presents C6 type inlet."2 " means C8 type inlet.

William R. Carroy

William R. Carney, Director, North American Certification Programs

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, pleas contact a local UL Customer Service Representative at www.ul.com/contactus

