



Ref. Certif. No.

**SE-84804**

**IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME**

**CB TEST CERTIFICATE**

Product

ITE POWER SUPPLY

Name and address of the applicant

GlobTek, Inc.  
186 Veterans Dr. Northvale, NJ 07647 USA

Name and address of the manufacturer

Same as applicant

Name and address of the factory

Note: When more than one factory, please report on page 2

See page 2

Ratings and principal characteristics

Input: 100 - 240Vac, 50-60 Hz, 0.3 A, Class II  
Output: 3.3 - 24Vdc, 1.8 A max

Trademark (if any)



Customer's Testing Facility (CTF) Stage used

-

Model / Type Ref.

GT-41134-\*\*\*, GT-41134-\*\*\*-W2\*, GT-41134-\*\*\*-W2\*-USB

Additional information (if necessary may also be reported on page 2)

See page 2

A sample of the product was tested and found to be in conformity with

IEC 60950-1:2005+A1+A2  
(EN 60950-1:2006 and A11+A1+A12+A2)

As shown in the Test Report Ref. No. which forms part of this Certificate

160901564SHA-001

This CB Test Certificate is issued by the National Certification Body

**Intertek Semko AB**  
Box 1103  
SE-164 22 Kista, Sweden  
Int +46 8 750 00 00

Date: 28 October 2016

**Intertek**

Signature:

Gary Hu

**Factories**

1. GlobTek, Inc.  
186 Veterans Dr. Northvale, NJ 07647 USA
2. GlobTek (Suzhou) Co., Ltd  
Building 4, No. 76, Jin Ling East Rd., Suzhou Industrial Park, Suzhou, JiangSu 215021, China

**Additional information (if necessary)**

Group differences for the CENELEC countries, national Differences of Korea, Canada, Israel, USA, China, Australia and New Zealand have been checked.

Explanation of model designation GT-41134-\*\*\*, GT-41134-\*\*\*-W2\*-USB and GT-41134-\*\*\*-W2\*:

The 1st "\*" denote the rated output wattage designation, which can be "01" to "06".

The 2nd "\*" denote the standard rated output voltage designation, which can be "03", "04", "06", "12", "15", "18" or "24";

The 3rd "\*" is the optional deviation, added or subtracted from standard output voltage, which can be "-0.1" to "-9.9" with interval of 0.1, or blank to indicate no voltage different.

The 2nd "\*" and 3rd "\*" together denote the output voltage, with a maximum value of 24V.

The 4th "\*" of GT-41134-\*\*\*-W2\*-USB and GT-41134-\*\*\*-W2\* series denotes type of plug and can be E for European plug, U for United Kingdom plug, blank for US plug, C for Chinese plug, A for Australia plug.

Date: 28 October 2016

Signature: 