



Ref. Certif. No.

SE-111934

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

ICT/ITE Power Supply

Name and address of the applicant

GlobTek, Inc.
186 Veterans Drive Northvale NJ 07647, USA

Name and address of the manufacturer

Same as applicant

Name and address of the factory

☒ Additional Information on page 2

Note: When more than one factory, please report on page 2

Ratings and principal characteristics

See page 2

Trademark / Brand (if any)

 **GlobTek, Inc.**

Customer's Testing Facility (CTF) Stage used

-

Model / Type Ref.

GT-43004P***-T*

Additional information (if necessary may also be reported on page 2)

☒ Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 62368-1:2018

As shown in the Test Report Ref. No. which forms part of this Certificate


230501954SHA-001

This CB Test Certificate is issued by the National Certification Body

Intertek Semko AB
Torshamnsgatan 43
Box 1103
SE-164 22 Kista, Sweden
Date: 29 August, 2023

intertek

Signature:



Gary Hu

Factories

1. GlobTek, Inc.
186 Veterans Drive Northvale NJ 07647, USA

2. GlobTek (Suzhou) Co., Ltd
Building 4, No. 76 JinLing East Road, Suzhou Industrial Park, Suzhou, JiangSu, 215021, China

Ratings and principal characteristics

Input: 100-240V~, 50-60Hz, 2.0A;

Output:

Model	Rated output voltage range	Max. rated output current	Max. rated output power
GT-43004P*12*-T*	12V	10A	120W
GT-43004P*16*-T*	12.1-16V	10A	120W
GT-43004P*19*-T*	16.1-19V	7.45A	120W
GT-43004P*24*-T*	19.1-24V	7.85A	150W

Additional information

Explanation of model GT-43004P***-T*:

The 1st symbol "***" part denotes the rated output wattage designation, which can be "001" to "150", with interval of 1.

The 2nd symbol "**" part denotes the standard rated output voltage designation, which can be "12", "16", "19", "24".

The 3rd symbol "*" part is optional, which can be "-0.1" to "-4.9" with interval of 0.1 to denote voltage deviation or blank to indicate no voltage different. The result by subtracting the deviation value from the standard rated output voltage denotes the rated output voltage, with a range of 12-24volts.

The 4th symbol "T*" part can be '2' to denote Class II model with standard sheet C8 appliance inlet, or '3' and '3A' to denote two types of Class I models with standard sheet C14 or standard sheet C6 appliance inlets.

The group and national differences for the CENELEC countries, and the national differences for USA, Canada, Australia, New Zealand and Singapore have been checked.

Date: 29 August, 2023

Signature: 