

Order No. 195248

Page 1/2

Product Switching power supply

Applicant GlobTek, Inc.
186 Veterans Drive
Northvale, NJ 07647
USA

Manufacturer GlobTek, Inc.
186 Veterans Drive
Northvale, NJ 07647
USA

Factory ☒ See page 2

Ratings 2.0A 100-240Vac 50-60Hz

Trade mark GlobTek

Model / Type Ref. GT-43004PWWVVV-X.X-TZ

Principal characteristics Cl. I. More information see page 2
☐ See next page(s)

A sample of the product was tested and found to be in conformity with OFF EN 60950-1:2006;A11;A1;A12

Validity This certificate documents conformity with the standards shown, and also applies as license for use of Nemkos name and certification mark. The certificate and license is valid as long as the applicable conditions are complied with, and provided that any changes to the product are notified to Nemko for acceptance prior to implementation. New standards or amendments to the standards may imply that the product design must be updated and/or that re-testing and re-certification is necessary.

Additional information ☒ Additional information on page 2

Additional model(s) Compliance with requirements regarding electromagnetic compatibility (EMC) is based on a self declaration from the manufacturer/representative according to the European EMC Directive.
☐ See next page(s)

Date of issue 08-08-2012



Signature

Juan Z. Kleppenes

Certification Department

Nemko AS

Office address

Internet

Telephone

Fax

P.O. Box 73, Blindern

Gaustadalléen 30

www.nemko.com

+47 22 96 03 30

+ 47 22 96 05 50

N-0314 Oslo, Norway

Oslo

Enterprise number:

NO 974404532

Factories:

Á
Á
Á
Á
Á

GlobTek, Inc.
186 Veterans Drive
Northvale, NJ 07647
USA

GlobTek (Suzhou) Co., Ltd
Building 4, No. 76, Jin Ling East Rd., Suzhou Industrial
Park,
Suzhou, JiangSu 215021
China

Additional information

Maximum ambient temperature 25°C. Output: Max. 150W, Max. 10A.
12-24Vdc. In model name, the WWW denotes the watt, which can be
100-150, max. 150W; the VV denotes the output voltage, which can be
"12-24"; the -X.X denotes the optional deviation, subtracted from standard
output voltage in 0.1 volt increments or blank to indicate the no voltage
different; Z presents different inlets, where "3" presents C14, "3A" presents
C6.

Date of issue 08-08-2012



Signature

Juan Z. Kleppen

Certification Department

Nemko AS	Office address	Internet	Telephone	Fax
P.O. Box 73, Blindern	Gaustadalléen 30	www.nemko.com	+47 22 96 03 30	+ 47 22 96 05 50
N-0314 Oslo, Norway	Oslo		Enterprise number:	NO 974404532