

Order No. 229385

Page 1/2

Product	Switching power adapter
Applicant	GlobTek, Inc. 186 Veterans Drive Northvale, NJ 07647 USA
Manufacturer	GlobTek, Inc. 186 Veterans Drive Northvale, NJ 07647 USA
Factory	<input checked="" type="checkbox"/> See page 2
Ratings	Input: 1.0A 100-240Vac 50-60Hz
Trade mark	GlobTek
Model / Type Ref.	GT-43007-WWVV-X.X
Principal characteristics	<input checked="" type="checkbox"/> See page 2
A sample of the product was tested and found to be in conformity with	OFF EN 60950-1:2006;A11;A1;A12
Validity	This certificate documents conformity with the standards shown, and also applies as license for use of Nemkos name and certification mark. The certificate and license is valid as long as the applicable conditions are complied with, and provided that any changes to the product are notified to Nemko for acceptance prior to implementation. New standards or amendments to the standards may imply that the product design must be updated and/or that re-testing and re-certification is necessary.
Additional information	<input type="checkbox"/> See next page(s) Compliance with requirements regarding electromagnetic compatibility (EMC) is based on a self declaration from the manufacturer/representative according to the European EMC Directive.
Additional model(s)	<input type="checkbox"/> See next page(s)

Date of issue 29-01-2013



Signature

Juan Z. Kleppenes

Certification Department

Nemko AS

Office address

Internet

Telephone

Fax

P.O. Box 73, Blindern

Gaustadalléen 30

www.nemko.com

+47 22 96 03 30

+ 47 22 96 05 50

N-0314 Oslo, Norway

Oslo

Enterprise number:

NO 974404532

Factories:

GlobTek, Inc.
186 Veterans Drive
Northvale, NJ 07647
USA

Á
Á
Á
Á
Á
Á

GlobTek (Suzhou) Co., Ltd
Building 4, No. 76, Jin Ling East Rd., Suzhou Industrial
Park, Suzhou, JiangSu 215021
China

Principal characteristics

Cl. II. Output: 12-24Vdc, Max. 40.08W, Max. 3.0A. In model name, the WW denotes the watt, with a maximum value of "40" denotes max. 40.08W; The VV denotes the output voltage, which can be "12-24"; The X.X denotes the optional deviation, subtracted from standard output voltage in 0.1 volt increments or blank to indicate the no voltage different; The VV-X.X together denote the output voltage, with a range of 12-24V.

Date of issue 29-01-2013



Signature

Juan Z. Kleppen

Certification Department

Nemko AS

Office address

Internet

Telephone

Fax

P.O. Box 73, Blindern

Gaustadalléen 30

www.nemko.com

+47 22 96 03 30

+ 47 22 96 05 50

N-0314 Oslo, Norway

Oslo

Enterprise number:

NO 974404532