



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO.: 2015010907828855

Valid from: Nov.07,2023

Valid until: Dec.16,2025

**NAME AND REGISTERED
ADDRESS OF THE APPLICANT**

GlobTek,Inc.
186 Veterans Dr. Northvale, NJ 07647 / USA

**NAME AND REGISTERED
ADDRESS OF THE
MANUFACTURER**

GlobTek,Inc.
186 Veterans Dr. Northvale, NJ 07647 / USA

**NAME AND LOCATION
OF THE FACTORY**

GlobTek (Suzhou) Co., Ltd
Building 4, No. 76 JinLing East Road,Suzhou Industrial Park, Suzhou, JiangSu, 215021, China.

PRODUCT MODEL(S)

ITE POWER SUPPLY
See appendix (Altitude up to 5000m)

**STANDARDS AND
TECHNICAL REQUIREMENTS**

GB 17625.1-2022 (Class A) ;GB 4943.1-2022;GB/T 9254.1-2021

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification(REFNO. CNCA-C09-01:2023)

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

Date of original issued: Dec.16,2015

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P

The certificate information is available through the QR code below or CNCA's website: www.cnca.gov.cn



SIGNATURE:

谢肇煦



CHINA QUALITY CERTIFICATION CENTRE



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2015010907828855

page 1 of 1

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

GT-46060-WWVV-X.XX*****, WW is the standard output wattage, with a maximum value of "06". VV is the standard rated output voltage designation, with a maximum value of "24"; which can be 05,06,09,12,15,18,24. -X.XX is optional, which can be "-0.01" to "-5.99", denote the output voltage differentiator, subtracting X.XX volts from standard output voltage VV in 0.01V increments, the actual output voltage rang is 5-24V, blank is to indicate the no voltage different. Each * = 0-9 or A-Z or () - or blank for marketing purposes, not affect safety.
Input: 100-240V~,50-60Hz,0.3A, Output:5-24Vdc, Max. 6W, Max.1.2A

See list

Model	DC output voltage	Maximum output current	Maximum output power
GT-46060-WW05*****	5V	1.2A	6W
GT-46060-WW06-X.XX*****	5.1-6V	1.18A	6W
GT-46060-WW09-X.XX*****	6.1-9V	0.98A	6W
GT-46060-WW12-X.XX*****	9.1-12V	0.66A	6W
GT-46060-WW15-X.XX*****	12.1-15V	0.5A	6W
GT-46060-WW18-X.XX*****	15.1-18V	0.4A	6W
GT-46060-WW24-X.XX*****	18.1-24V	0.33A	6W



CHINA QUALITY CERTIFICATION CENTRE