

Ref. Certif. No.
SE-100946

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Name and address of the applicant

Name and address of the manufacturer

Name and address of the factory
Note: When more than one factory, please report on page 2

Ratings and principal characteristics

Trademark (if any)

Customer's Testing Facility (CTF) Stage used

Model / Type Ref.

Additional information (if necessary may also be reported on page 2)

A sample of the product was tested and found to be in conformity with

As shown in the Test Report Ref. No. which forms part of this Certificate


ICT/ITE POWER SUPPLY

GlobTek, Inc.
186 Veterans Drive, NJ 07647 Northvale, USA

Same as applicant

See page 2

I/P: 100-240 V~, 50-60 Hz, 0.6 A, Class II
O/P: 5-48 VDC, max. 2.4 A, max. 12 W



-

GT-46120-***-W2*****


See page 2


IEC 62368-1:2014

200300279TWN-001

This CB Test Certificate is issued by the National Certification Body

Intertek Semko AB
Torshamnsgatan 43
Box 1103
SE-164 22 Kista, Sweden



Signature: 

Date: 30 April, 2020

Ted Wu

Factories

GlobTek (Suzhou) Co., Ltd.
Building 4, No.76, JinLing East Road, Suzhou Industrial Park, Suzhou, Jiangsu 215021, China

GlobTek, Inc.
186 Veterans Drive, NJ 07647 Northvale, USA

Additional information

Explanation of model GT-46120-***-W2*****:

The 1st symbol "***" is the standard output wattage, with a maximum value of "12".

The 2nd symbol "***" is the standard rated output voltage designation, with a maximum value of "48", which can be 05, 06, 09, 12, 15, 24, 36, 48.

The 3rd symbol "***" denote the output voltage differentiator, subtracted from standard output voltage, which can be "-0.01" to "-11.99" with interval of 0.01, the actual output voltage range is 5-48 VDC, blank is to indicate the no voltage different.

The 4th symbol "***" denote type of plug and can be E for European plug, U for British plug, blank for North American / Japan/Taiwan plug, C for Chinese plug, A for Australia plug.

-W2* can be optional, when it is blank, denote to be with replaceable plug

The last six symbols "***" can be 0-9 or A-Z, "(", ")", "[", "]", "-", or blank for marketing purposes.

The national differences for AU, DK, JP, NZ, IT and US have been checked.

The product has also been checked according to EN 62368-1:2014+A11.

Date: 30 April, 2020

Signature:

