

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE	
Product	ICT/ITE Power Supply
Name and address of the applicant	GlobTek, Inc. 186 Veterans Drive Northvale NJ 07647 United States of America
Name and address of the manufacturer	GlobTek, Inc. 186 Veterans Drive Northvale NJ 07647 United States of America
Name and address of the factory	See next page(s)
Note: When more than one factory,please report on page 2	Additional Information on Page 2
Ratings and Principal characteristics Trademark /Brand (If any)	I/P: 100-240Vac, 50-60Hz or 50/60Hz, 0.6A
Customer's Testing Facility (CTF) Stage used	
Model/Type Ref	GT-46180-WWVV-X.XX****** series (Replaceable plug), GT-46182- WWVV-X.XX-W2Z****** series (Fixed plug)
Additional information(If necessary may also be reported on Page 2)	Additional Information on Page 2
A sample of the product was tested and found to be in conformity with	IEC 62368-1:2018
As shown in the Test Report Ref. No. which forms part of this Certificate	REP012224
This CB Test Certificate is issued by the National Certification Body	
Nemko	

Philip Pedersen vei 11, NO-1366 Lysaker, Norway Date: 05-07-2023

Signature: Juan Z Saussey Certification department

Disclaimer: This document is controlled and has been released electronically. Only the version on the IECEE Website is the current document version



GlobTek, Inc. 186 Veterans Drive Northvale NJ 07647 United States of America GlobTek (Suzhou) Co., Ltd Building 4, No. 76, Jin Ling East Rd., Suzhou Industrial Park, Suzhou,JiangSu 215021 China

Additional Information (if necessary)

O/P: referring to the test report

In model name: WW is the standard output wattage, with a maximum value of '18'.

VV is the standard rated output voltage designation, with a maximum value of '24'; which can be 05, 09, 12, 15, 18, 24.

-X.XX is optional, which can be '-0.01' to '-5.99', denote the output voltage differentiator, subtracting

-X.XX volts from standard output voltage VV in 0.01V increments, the actual output voltage range is 5-24Vdc, blank is to indicate the no voltage different.

Each * = 0-9 or A-Z or ()[] or blank for marketing purposes.

Z designates type of plug and can be E for European plug, U for British plug, blank for North American / Japan plug/Taiwan plug, C for Chinese plug, A for Australia plug, K for Korean plug



Philip Pedersen vei 11, NO-1366 Lysaker, Norway Date: 05-07-2023

Signature: Juan Z Saussey Certification department

Disclaimer: This document is controlled and has been released electronically. Only the version on the IECEE Website is the current document version