

# CERTIFICATE OF COMPLIANCE

**Certificate Number** E341351  
**Report Reference** E341351-20180912  
**Issue Date** 2020-AUGUST-28

**Issued to:** GLOBTEK (HONG KONG) LTD  
UNIT 1402, BENSON TOWER  
74 HUNG TO RD  
KWUN TONG  
KOWLOON HONG KONG

**This certificate confirms that  
representative samples of**

POWER SUPPLIES FOR USE WITH AUDIO/VIDEO,  
INFORMATION AND COMMUNICATION TECHNOLOGY  
EQUIPMENT  
SEE ADDENDUM PAGE

Have been investigated by UL in accordance with the  
Standard(s) indicated on this Certificate.


**Standard(s) for Safety:** UL 62368-1 and CSA C22.2 No. 62368-1-14, Audio/video,  
Information and Communication Technology Equipment -  
Part 1: Safety Requirements

**Additional Information:** See the UL Online Certifications Directory at  
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** E341351  
**Report Reference** E341351-20180912  
**Issue Date** 2020-AUGUST-28

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

## ICT/ITE POWER SUPPLY

GT-46181-\*\*\*-T\*\*

The 1st “\*” denotes the rated output wattage, with a maximum value of “18”,


The 2nd “\*” denotes the standard rated output voltage designation, with a value of “05”, “09”, “12”, “15”,

The 3rd “\*” is optional deviation, subtracted from standard output voltage, which can be “-0.1” to “-3.9” with interval of 0.1, or blank to indicate no voltage different,

The 2nd and 3rd together denote the output voltage, with a range of 5-15Vdc

The 4th “\*” can be 3 or 3A, 3 means C14 inlet type, 3A means C6 inlet type.

The last \* denote any six character = 0-9 or A-Z or ()[] or – or blank for marketing purposes.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

