

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

ICT/ITE Power Supply

Name and address of the applicant

GlobTek, Inc.
186 Veterans Drive, Northvale NJ 07647,
New Jersey, USA

Name and address of the manufacturer

GlobTek, Inc.
186 Veterans Drive, Northvale NJ 07647,
New Jersey, USA

Name and address of the factory


See page 2

Note: When more than one factory, please report on page 2

Ratings and principal characteristics

☒ Additional Information on page 2Input: 100-240 V~; 50-60 Hz; 0,5 A
Output: 5-5,95 Vdc; max. 4 A; max. 20 W (see page 2 for details)

Trademark / Brand (if any)

 **GlobTek, Inc.**

Customer's Testing Facility (CTF) Stage used

/

Model / Type Ref.

GT-46200-WWVV-X.XX-TZ*****
(see page 2 for details)

Additional information (if necessary may also be reported on page 2)

Unit also complies with EN 62368-1:2014 + A11:2017

A sample of the product was tested and found to be in conformity with

☒ Additional Information on page 2

IEC 62368-1:2014

As shown in the Test Report Ref. No. which forms part of this Certificate

T223-0042/20 (2020-04-10)


This CB Test Certificate is issued by the National Certification Body

SIQ Ljubljana, Mašera-Spasičeva ulica 10, SI-1000 Ljubljana, Slovenia
T +386 1 4778 100, F +386 1 4778 444, info@siq.si, www.siq.si

SIQ Ljubljana is accredited by Slovenian Accreditation with accreditation number CP-001 in the field of certification of products, processes and services.

Date: 2020-04-10

Signature: Bojan Pečavar



Name and address of the factories:

1) GlobTek, Inc.
186 Veterans Drive, Northvale NJ 07647,
New Jersey, USA

2) GlobTek (Suzhou) Co. Ltd.
Building 4, No. 76 JinLing East Road, Suzhou Industrial Park,
Suzhou JiangSu, 215021,
China

Ratings and principal characteristics:

GT-46200 series model list:

GT-46200-WWVV-X.XX-TZ*****

WW is the standard output wattage, with a maximum value of "20",

VV is the standard rated output voltage designation, with a value of "05" and "06";

-X.XX denote the output voltage differentiator, subtracting X.XX volts from standard output voltage
VV in 0.01V increments, the actual output voltage rang is 5 – 5,95 V, blank is to indicate the no
voltage different.

Z can be 2 or 3 or 3 A, 2 means Class II with C8 inlet type, 3 means Class I with C14 inlet type, 3A
means Class I with C6 inlet type

Each * = 0-9 or A-Z or ()[] or blank for marketing purposes.

Model name	Output voltage (Vdc)	Output current (A)	Max. power (VA)
GT-46200-WW05-TZ*****	5	4.0	20
GT-46200-WW06-X.XX-TZ*****	5.01 - 5.95	3.59	18

Additional information (if necessary)

Date: 2020-04-10

Signature: Bojan Pečavar

