

CERTIFICATE OF COMPLIANCE

Certificate Number E341351
Report Reference E341351-A6004-UL
Issue Date 2020-AUGUST-27

Issued to: GLOBTEK (HONG KONG) LTD
UNIT 1402, BENSON TOWER
74 HUNG TO RD
KWUN TONG
KOWLOON HONG KONG

**This certificate confirms that
representative samples of**

POWER SUPPLIES FOR USE WITH AUDIO/VIDEO,
INFORMATION AND COMMUNICATION TECHNOLOGY
EQUIPMENT
SEE ADDENDUM PAGE

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.


Standard(s) for Safety: UL 62368-1 and CAN/CSA C22.2 No. 62368-1-14,
Audio/video, information and communication technology
equipment Part 1: Safety requirements

Additional Information: See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number E341351
Report Reference E341351-A6004-UL
Issue Date 2020-AUGUST-27

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

ICT/ITE POWER SUPPLY

GT-46200-***-T**

The 1st “*” denotes the rated output wattage, with a maximum value of “20”,


The 2nd “*” denotes the standard rated output voltage designation, with a value of “05” and “06”,

The 3rd “*” is optional deviation, subtracted from standard output voltage, which can be “-0.05” to “-0.99” with interval of 0.01, or blank to indicate no voltage different,

The 2nd and 3rd together denote the output voltage, with a range of 5-5.95Vdc

The 4th “*” can be 3 or 3A, 3 means C14 inlet type, 3A means C6 inlet type.

The last * denote any six character = 0-9 or A-Z or ()[] or – or blank for marketing purposes.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

