

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

ITE POWER SUPPLY

Name and address of the applicant

GlobTek, Inc.
186 Veterans Drive, Northvale NJ 07647, New Jersey,
USA

Name and address of the manufacturer

GlobTek, Inc.
186 Veterans Drive, Northvale NJ 07647, New Jersey,
USA

Name and address of the factory

See next page.

Note: When more than one factory, please report on page 2

Ratings and principal characteristics

☒ Additional Information on page 2Input: 100-240 V~; 50-60 Hz; 1.0 A
Output: 12-24 Vdc; Max. 3 A; Max. 40 W

Trademark / Brand (if any)

 **GlobTek, Inc.**

Customer's Testing Facility (CTF) Stage used

Model / Type Ref.

GT-46400-WWV-X.X-TZ (see next page for nomenclature)

Additional information (if necessary may also
be reported on page 2)

Unit also complies with EN 62368-1:2014 + A11:2017.

A sample of the product was tested and found
to be in conformity with☐ Additional Information on page 2

IEC 62368-1:2014 (Second Edition)

As shown in the Test Report Ref. No. which
forms part of this Certificate


T223-0024/21, dated 2021-05-19

This CB Test Certificate is issued by the National Certification Body

SIQ Ljubljana, Mašera-Spasičeva ulica 10, SI-1000 Ljubljana, Slovenia
T +386 1 4778 100, F +386 1 4778 444, info@siq.si, www.siq.siSIQ Ljubljana is accredited by Slovenian Accreditation with accreditation number CP-001 in the
field of certification of products, processes and services.

Date: 2021-05-19

Signature: Bojan Pečavar



Factory locations (continued):

- 1) GlobTek, Inc. 186 Veterans Dr. Northvale, NJ 07647, New Jersey USA
- 2) GlobTek (Suzhou) Co. Ltd.,
Building 4, No. 76 JinLing East Road, Suzhou Industrial Park,
Suzhou JiangSu, 215021, China

Ratings and principal characteristics (continued):

GT-46400-WWVV-X.X-TZ

WW is the standard output wattage, with a maximum value of "40",

VV is the standard rated output voltage designation, with a value of "12" "15" "19" and "24";

-X.X denote the output voltage differentiator, subtracting X.X volts from standard output voltage VV in 0.1V increments, the actual output voltage range is 12-24Vdc, blank is to indicate the no voltage different.

Z can be 2 or 3 or 3A, 2 means C8 inlet type, 3 means C14 inlet type, 3A means C6 inlet type.

Model	Output Voltage	Max. Output current	Max. power
GT-46400-WW12-TZ	12V	3A	36W
GT-46400-WW15-X.X-TZ	12.1~15V	3A	40W
GT-46400-WW19-X.X-TZ	15.1~19V	2.66A	40W
GT-46400-WW24-X.X-TZ	19.1~24V	2.1A	40W

Additional information (if necessary)

Date: 2021-05-19

Signature: Bojan Pečavar

