

# Licence

## for the use of SIQ certification mark

**Number:** SI-SIQ 063/095 **Project file:** C20210058

**Product:** ITE Power Supply

**Type reference:** GT-46400-WWVV-X.X-TZ (See next page for nomenclature)


**Trademark:**  **GlobTek, Inc.**

**Ratings:** Input : 100-240 V~; 50-60 Hz; 1.0 A  
Output: 12-24 Vdc; Max. 3 A; Max. 40 W

**Applicant / Licensee:** **GlobTek, Inc.**  
**186 Veterans Drive, Northvale NJ 07647, New Jersey, USA**

**Manufacturer:** GlobTek, Inc.  
186 Veterans Drive, Northvale NJ 07647, New Jersey, USA

SIQ hereby grants the right to use the SIQ certification mark of conformity on the products specified in this document. The SIQ certification mark of conformity signifies the compliance of the products with requirements of cited standards.

**Certification mark:** 

**Standard:** EN 62368-1:2014 + A11:2017

**Test report:** T223-0024/21

**Remarks:** This licence has been issued under the presumption and conditional on the fact that the licensee holds all necessary legal rights with regard to the product presented for testing and certification.  
This licence is valid as long as the conditions laid down in the listed standards are not modified significantly and until the licensee complies with the SIQ's rules on product certification.

**Date:** 2021-05-19

**Authorized signature:** Bojan Pečavar



*Only integral publication of this licence is allowed. This licence may only be reproduced in its entirety and without any changes. On request SIQ will give information about the validity of the licence.*

# Licence

## for the use of SIQ certification mark

**Number:** SI-SIQ 063/095

### Additional remarks:

The list of critical components of the product for which this licence is granted is included in the test report.

### Type reference (continued):

GT-46400-WWVV-X.X-TZ

WW is the standard output wattage, with a maximum value of "40",

VV is the standard rated output voltage designation, with a value of "12" "15" "19" and "24";

-X.X denote the output voltage differentiator, subtracting X.X volts from standard output voltage VV in 0.1V increments, the actual output voltage range is 12-24Vdc, blank is to indicate the no voltage different.

Z can be 2 or 3 or 3A, 2 means C8 inlet type, 3 means C14 inlet type, 3A means C6 inlet type.

Model	Output Voltage	Max. Output current	Max. power
GT-46400-WW12-TZ	12V	3A	36W
GT-46400-WW15-X.X-TZ	12.1~15V	3A	40W
GT-46400-WW19-X.X-TZ	15.1~19V	2.66A	40W
GT-46400-WW24-X.X-TZ	19.1~24V	2.1A	40W

### Places of manufacture, inspection file number:

1) GlobTek, Inc.  
186 Veterans Dr. Northvale, NJ 07647, New Jersey  
USA  
[15994-15994]

2) GlobTek (Suzhou) Co. Ltd.  
Building 4, No. 76 JinLing East Road, Suzhou Industrial Park, Suzhou JiangSu, 215021, China  
[15994-27052]

### Limitation:

/

**Date:** 2021-05-19

**Authorized signature:** Bojan Pečavar

