



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO.: 2016010907835354

Valid from: Mar.30,2023

Valid until: Dec.23,2025

**NAME AND REGISTERED
ADDRESS OF THE APPLICANT**

GlobTek,Inc.
186 Veterans Dr. Northvale, NJ 07647 / USA

**NAME AND REGISTERED
ADDRESS OF THE
MANUFACTURER**

GlobTek,Inc.
186 Veterans Dr. Northvale, NJ 07647 / USA

**NAME AND LOCATION
OF THE FACTORY**

GlobTek (Suzhou) Co., Ltd
Building 4, No. 76 JinLing East Road,Suzhou Industrial Park, Suzhou, JiangSu, 215021, China.

PRODUCT MODEL(S)

ITE POWER SUPPLY
See appendix (Altitude up to 5000m) (Sale without cord set)

**STANDARDS AND
TECHNICAL REQUIREMENTS**

GB 17625.1-2012;GB 4943.1-2022;GB/T 9254.1-2021

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification(REFNO. CNCA-C09-01:2014)

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

Date of original issued: Jan.06,2016

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P

The certificate information is available through the QR code below or CNCA's website: www.cnca.gov.cn



SIGNATURE:

谢肇煦



CHINA QUALITY CERTIFICATION CENTRE



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2016010907835354

page 1 of 1

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

GT-46600-WWVV-X.X-T2*(WW ranges from 01 to 65, and the step is 1, indicating the rated output power; VV is 12, 15, or 24. X.X can be blank or "0.1" to "8.9" with a step of 0.1. The difference between VV and X.X represents the rated output voltage, ranging from 12-24V. When the rated output voltage is 12V or 15V or 24V, -X.X is blank; "*" represents an arbitrary mix of six figures for "0-9" or "a-z" or "(" or "[]" or "-" or blank, on behalf of the market purpose)

Input : 100-240V ~, 50-60Hz, 1.5A.

Output : 12-24V, Max. 65W.

Model	DC output voltage	Maximum output current	Maximum power
GT-46600-WW12-T2	12V	5A	60W
GT-46600-WW15-X.X-T2	12.1~15V	5A	60W
GT-46600-WW24-X.X-T2	15.1~18.9V	4A	60W
GT-46600-WW24-X.X-T2	19~24V	3.42A	65W



CHINA QUALITY CERTIFICATION CENTRE