



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO.: 2016010907836497

Valid from: Mar.30,2023

Valid until: Dec.23,2025

**NAME AND REGISTERED
ADDRESS OF THE APPLICANT**

GlobTek,Inc.
186 Veterans Dr. Northvale, NJ 07647 / USA

**NAME AND REGISTERED
ADDRESS OF THE
MANUFACTURER**

GlobTek,Inc.
186 Veterans Dr. Northvale, NJ 07647 / USA

**NAME AND LOCATION
OF THE FACTORY**

GlobTek (Suzhou) Co., Ltd
Building 4, No. 76 JinLing East Road,Suzhou Industrial Park, Suzhou, JiangSu, 215021, China.

PRODUCT MODEL(S)

ITE POWER SUPPLY
See appendix (Altitude up to 5000m , sale without cord set)

**STANDARDS AND
TECHNICAL REQUIREMENTS**

GB 17625.1-2012;GB 4943.1-2022;GB/T 9254.1-2021

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification(REFNO. CNCA-C09-01:2014)

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

Date of original issued: Jan.11,2016

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P

The certificate information is available through the QR code below or CNCA's website: www.cnca.gov.cn



SIGNATURE:

谢肇煦



CHINA QUALITY CERTIFICATION CENTRE



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2016010907836497

page 1 of 1

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

Model : GT-46600-WWVV-X.X-TZ*(WW ranges from 01 to 65, and the step is 1, indicating the rated output power; VV is 12, 15, or 24. X.X can be blank or "0.1" to "8.9" with a step of 0.1. The difference between VV and X.X represents the rated output voltage, ranging from 12-24V. When the rated output voltage is 12V or 15V or 24V, -X.X is blank; Z can be 3 or 3A for different appliance sockets; "*" represents an arbitrary mix of six figures for "0-9" or "a-z" or "()" or "[]" or "-" or blank, on behalf of the market purpose)

Input : 100-240V~, 50-60Hz, 1.5A.

Output : 12-24V, Max. 65W.

Model	DC Output voltage	DC output current	Maximum power
GT-46600-WW12-TZ	12V	5A	60W
GT-46600-WW15-X.X-TZ	12.1~15V	5A	60W
GT-46600-WW24-X.X-TZ	15.1~18.9V	4A	60W
GT-46600-WW24-X.X-TZ	19~24V	3.42A	65W



CHINA QUALITY CERTIFICATION CENTRE