CERTIFICATE OF COMPLIANCE

Certificate Number E341351

Report Reference E341351-20180612
Issue Date 2020-AUGUST-28

Issued to: GLOBTEK (HONG KONG) LTD

UNIT 1402, BENSON TOWER

74 HUNG TO RD KWUN TONG

KOWLOON HONG KONG

This certificate confirms that representative samples of

POWER SUPPLIES FOR USE WITH AUDIO/VIDEO, INFORMATION AND COMMUNICATION TECHNOLOGY

EQUIPMENT

SEE ADDENDUM PAGE

Have been investigated by UL in accordance with the

Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 62368-1 and CSA C22.2 No. 62368-1-14, Audio/video,

Information and Communication Technology Equipment -

Part 1: Safety Requirements

Additional Information: See the UL Online Certifications Directory at

https://ig.ulprospector.com for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/



CERTIFICATE OF COMPLIANCE

Certificate Number E341351

Report Reference E341351-20180612 Issue Date 2020-AUGUST-28

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

ICTICT/ITE POWER SUPPLY

GT-46600-WWVV-X.X-T2*

WW is the standard output wattage, with a maximum value of "65", VV is the standard rated output voltage designation, with a value of "12" "15"and "24";

-X.X denote the output voltage differentiator, subtracting X.X volts from standard output voltage VV in 0.1V increments, the actual output voltage range is 12-24V, blank is to indicate the no voltage different.

The last "*" denote any six character means "0-9", "A-Z","()", "[]","—" or blank for marketing purposes.

Ba Mally

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, pleas contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

