

CB TEST CERTIFICATE CERTIFICAT D'ESSAI OC

Product
ProduitName and address of the applicant
Nom et adresse du demandeurName and address of the manufacturer
Nom et adresse du fabricantName and address of the factory
Nom et adresse de l'usineNote: When more than one factory, please report on page 2
Note: Lorsque il y plus d'une usine, veuillez utiliser la deuxième pageRatings and principal characteristics
Valeurs nominales et caractéristiques principalesTrademark (if any)
Marque de fabrique (si elle existe)Type of Manufacturer's Testing Laboratories used
Type de programme du laboratoire d'essais constructeurModel / Type Ref.
Ref. De typeAdditional information (if necessary may also be reported on page 2)
Les informations complémentaires (si nécessaire, peuvent être indiqués sur la deuxième page)

A sample of the product was tested and found to be in conformity with
Un échantillon de ce produit a été essayé et a été considéré conforme à la

As shown in the Test Report Ref. No. which forms part of this Certificate

Switching Power Adapter

GlobTek, Inc.
186 Veterans Drive
Northvale, NJ 07647
USA

GlobTek, Inc.
186 Veterans Drive
Northvale, NJ 07647
USA

☒ Additional information on page 2

Input: 1.5A, AC100-240V, 50/60Hz, Cl. I & Cl. II



GT-81081-60x-y-a-CC

IP20; Output: 12Vdc-24Vdc, Max.5. The "x" is the rated standard output voltage designation, which can be 12, 14, 15, 18, 19, 20, 22 or 24; "y" is minor adjusting variable to standard output voltage, which can be 0.1 - 2.9 in step of 0.1 or blank; "a" represents the inlet type, which can be T2 or T3 or T3A; T2 represents C8 inlet type (Class II construction), T3 represents C14 inlet type (Class I construction), T3A represents C6 inlet type (Class I construction). "-CC" is optional, the model name with suffix "-CC" means it has different control method of secondary voltage. The model GT-81081-60x-y-a is similar to GT-81081-60x-y-a-CC except the model number and the secondary voltage control method, the GT-81081-60x-y-a used U3, C17, R35 and D6 in secondary circuit to control the secondary voltage, and GT-81081-60x-y-a-CC used U2-A, U2-B, C13, C14, C15, C16, R27, R28, R29, R30, R32, R33 and R34 in secondary circuit to control the secondary voltage.

☐ Additional information on page 2

IEC 60950-1(ed.2);am1;am2

267717



Gaustadalléen 30
NO-0373 Oslo, Norway

Date: 10-09-2014

Signature: Juan Z. Kleppenes
Certification Department



Ref. Certif. No.

NO82491

Comme indiqué dans le Rapport d'essais numéro de
référence qui constitue partie de ce Certificat

This CB Test Certificate is issued by the National Certification Body

Ce Certificat d'essai OC est établi par l'Organisme **National de Certification**



Gaustadalléen 30
NO-0373 Oslo, Norway

Date: 10-09-2014

Signature: Juan Z. Kleppenes
Certification Department



Ref. Certif. No.

NO82491

GlobTek, Inc.
186 Veterans Drive
Northvale, NJ 07647
USA

GlobTek (Suzhou) Co., Ltd
Building 4, No. 76, Jin Ling East Rd., Suzhou Industrial
Park, Suzhou, JiangSu 215021
China



Gaustadalléen 30
NO-0373 Oslo, Norway

Date: 10-09-2014

Signature: Juan Z. Kleppenes
Certification Department