



Ref. Certif. No

NO131085

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

ICT/ITE Power Supply

Name and address of the applicant

GlobTek, Inc.
186 Veterans Drive
Northvale NJ 07647
United States of America

Name and address of the manufacturer

GlobTek, Inc.
186 Veterans Drive
Northvale NJ 07647
United States of America

Name and address of the factory

See next page(s)

Note: When more than one factory, please report on page 2

☒ Additional Information on Page 2

Ratings and Principal characteristics

AC Input: 1.5A 100-240Vac 50-60Hz or 50/60Hz,
Cl. I & Cl. II

Trademark /Brand (If any)



Customer's Testing Facility (CTF) Stage used

Model/Type Ref

GT-81081-60x-y-a-CC

Additional information (If necessary may also be reported on Page 2)

☒ Additional Information on Page 2

A sample of the product was tested and found to be in conformity with

IEC 62368-1:2018

As shown in the Test Report Ref. No. which forms part of this Certificate

REP021856

This CB Test Certificate is issued by the National Certification Body

Philip Pedersen vei 11,
NO-1366 Lysaker, Norway
Date: 10-06-2024Signature: Okhyun Jeon
Certification department



Ref. Certif. No

NO131085

GlobTek, Inc.
186 Veterans Drive
Northvale NJ 07647
United States of America

GlobTek (Suzhou) Co., Ltd
Building 4, No. 76, Jin Ling East Rd., Suzhou Industrial Park,
Suzhou, Jiangsu 215021
China

Additional Information (if necessary)

Output: See test report for details. In model name, the 'x' is the rated standard output voltage designation, which can be 12, 14, 15, 18, 19, 20, 22 or 24;

'y' is minor adjusting variable to standard output voltage, which can be 0.1 - 2.9 in step of 0.1 or blank;

'a' represents the inlet type, which can be T2 or T3 or T3A; T2 represents C8 inlet type (Class II construction), T3 represents C14 inlet type (Class I construction), T3A represents C6 inlet type (Class I construction);

'-CC' is optional, the model name with suffix '-CC' means it has different control method of secondary voltage.

The model GT-81081-60x-y-a is similar to GT-81081-60x-y-a-CC except the model number and the secondary voltage control method, the GT-81081-60x-y-a used U3, C17, R35 and D6 in secondary circuit to control the secondary voltage, and GT-81081-60x-y-a-CC used U2-A, U2-B, C13, C14, C15, C16, R27, R28, R29, R30, R32, R33 and R34 in secondary circuit to control the secondary voltage.



Philip Pedersen vei 11,
NO-1366 Lysaker, Norway
Date: 10-06-2024

Signature: Okhyun Jeon
Certification department