

**IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME****CB TEST CERTIFICATE**

Product

ICT/ITE Power Supply

Name and address of the applicant

GlobTek, Inc.  
186 Veterans Dr., Northvale, NJ 07647, New Jersey, USA

Name and address of the manufacturer

GlobTek, Inc.  
186 Veterans Dr., Northvale, NJ 07647, New Jersey, USA

Name and address of the factory

See page 2.


*Note: When more than one factory, please report on page 2*

Ratings and principal characteristics

☒ Additional Information on page 2

See page 2.

Trademark / Brand (if any)



Customer's Testing Facility (CTF) Stage used

/

Model / Type Ref.

GT-83084-WWVV-X.X-USB-W2Z  
(see page 2 for details)

Additional information (if necessary may also be reported on page 2)

Unit also complies with EN 62368-1:2014 + A11:2017

A sample of the product was tested and found to be in conformity with

☒ Additional Information on page 2

IEC 62368-1:2014

As shown in the Test Report Ref. No. which forms part of this Certificate

T223-0884/20 (2021-04-21)


This CB Test Certificate is issued by the National Certification Body

SIQ Ljubljana, Mašera-Spasičeva ulica 10, SI-1000 Ljubljana, Slovenia  
T +386 1 4778 100, F +386 1 4778 444, info@siq.si, www.siq.si

SIQ Ljubljana is accredited by Slovenian Accreditation with accreditation number CP-001 in the field of certification of products, processes and services.

Date: 2021-04-21

Signature: Bojan Pečavar





**Name and address of the factories:**

GlobTek, Inc.  
186 Veterans Dr., Northvale, NJ 07647, New Jersey, USA

GlobTek (Suzhou) Co., Ltd  
Building 4, No. 76, Jin Ling East Rd., Suzhou Industrial Park, Jiangsu 215021, China

**Ratings and principal characteristics:**

GT-83084-WWVV-X.X-USB-W2Z

"WW" is the standard output wattage, with a maximum value of "11";

"VV" is the standard rated output voltage designation, with a value of "06";

"-X.X" denote the output voltage differentiator, subtracting X.X volts from standard output voltage VV in 0.1V increments;

the actual output voltage range is 5V-5.2V, blank is to indicate the no voltage different;

"Z" designates type of plug and can be E for European plug, U for British plug, blank for North American / Japan plug/Taiwan plug, C for Chinese plug, I for India plug, A for Australia plug, K for Korea plug, AR for Argentina plug, BR for Brazilian plug, SA for South African plug.

GT-83084-WW06-1.0-USB-W2Z:

Input: 100 – 240 V~; 50/60 Hz; 0,3 A

Output: 5,0 V=; Max. 2,1 A

GT-83084-WW06-0.9-USB-W2Z:

Input: 100 – 240 V~; 50/60 Hz; 0,3 A

Output: 5,1 V=; Max. 2,1 A

GT-83084-WW06-0.8-USB-W2Z:

Input: 100 – 240 V~; 50/60 Hz; 0,3 A

Output: 5,2 V=; Max. 2,1 A

**Additional information (if necessary)**

Date: 2021-04-21

Signature: Bojan Pečavar

