



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO.: 2017010907979800

Valid from: Jun.09,2022

Valid until: May.26,2027

**NAME AND REGISTERED
ADDRESS OF THE APPLICANT**

GlobTek,Inc.
186 Veterans Dr. Northvale, NJ 07647 / USA

**NAME AND REGISTERED
ADDRESS OF THE
MANUFACTURER**

GlobTek,Inc.
186 Veterans Dr. Northvale, NJ 07647 / USA

**NAME AND LOCATION
OF THE FACTORY**

GlobTek (Suzhou) Co.,Ltd
Building 4, No. 76 JinLing East Road,Suzhou Industrial Park, Suzhou, JiangSu, China.

PRODUCT MODEL(S)

ITE POWER SUPPLY
See appendix (Altitude up to 5000m) (Sale without cord set)

**STANDARDS AND
TECHNICAL REQUIREMENTS**

GB 17625.1-2012;GB 4943.1-2011;GB/T 9254-2008

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification(REFNO. CNCA-C09-01:2014)

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

Date of original issued: Jul.03,2017

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P

The certificate information is available through the QR code below or CNCA's website: www.cnca.gov.cn



SIGNATURE:

谢肇煦



CHINA QUALITY CERTIFICATION CENTRE



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2017010907979800

page 1 of 1

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

Model: GT*96300-**-***

The 1st “*” part can be ‘M’ or ‘-’ or ‘H’ for market identification;

The 2nd “*” denotes the rated output wattage designation, which can be “01” to “36”, with interval of 1V.

The 3rd “*” denotes the standard rated output voltage designation, which can be “48”, “54” or “56”;

The 4th “*” can be T3 or T3A or R3A, T3 means C14 AC inlet, T3A and R3A means C6 AC inlet; The

5th “*” can be -AP or -PP or -SP, -AP (with baby board) stands for Active POE (full IEEE compliant),

-PP (no baby board) stands for Passive POE, -SP (no baby board) stands for Simple POE;

The last * denote any six character = 0-9 or A-Z or ()[] or – or blank for marketing purposes; The 1st “*” and 6th “*” do not affect product safety and EMC.

Input: 100-240Vac, 50-60Hz, 0.6A or 1.0A or 1.5A

Rating:

Models	Output Voltage (Vdc)	Max. Output Current (A)	Max. Output Power (W)
GT*96300-*48-T3/T3A/R3A-AP/PP/SP*	48	0.75	36
GT*96300-*54-T3/T3A/R3A-AP/PP/SP*	54	0.66	36
GT*96300-*56-T3/T3A/R3A-AP/PP/SP*	56	0.64	36



CHINA QUALITY CERTIFICATION CENTRE