

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME**CB TEST CERTIFICATE**

Product

ICT/ITE Power Supply

Name and address of the applicant

GlobTek, Inc.
186 Veterans Dr. Northvale, NJ 07647
UNITED STATES OF AMERICA

Name and address of the manufacturer

Same as applicant

Name and address of the factory

Note: When more than one factory, please report on page 2

See page 2

Ratings and principal characteristics

See page 2

Trademark (if any)



Customer's Testing Facility (CTF) Stage used

-

Model / Type Ref.

GT*96600-****, GT*91099-****, GT*96600-*56***

Additional information (if necessary may also be reported on page 2)

See page 3

A sample of the product was tested and found to be in conformity with

IEC 62368-1:2014

As shown in the Test Report Ref. No. which forms part of this Certificate

210301634SHA-001

This CB Test Certificate is issued by the National Certification Body

Intertek Semko AB
Torshamnsgatan 43
Box 1103
SE-164 22 Kista, Sweden**intertek**

Signature:



Date: 09 June, 2021

Hyden Li

Factories

GlobTek (Suzhou) Co., Ltd.
Building 4, No.76, JinLing East Road
Suzhou Industrial Park, Suzhou, 215021 Jiangsu
CHINA

GlobTek, Inc.
186 Veterans Dr. Northvale, NJ 07647
UNITED STATES OF AMERICA

Ratings and principal characteristics

GT*96600-****, GT*91099-****:
Input: 100-240V~, 50-60Hz or 50/60Hz, 1.5A;
Output: 5-54VDC, Max. 8.00A, Max. 65W

GT*96600-*56***:
Input: 100-240V~, 50-60Hz or 50/60Hz, 2.0A;
Output: 56VDC, Max. 70W

Date: 09 June, 2021

Signature:



Additional information

Group differences for CENELEC countries and national differences for Japan, Australia/New Zealand, US and Canadian are considered.

Model similarity:

GT*91099-*****

The 1st “*” part can be ‘M’ or ‘-’ or ‘H’ for market identification and not related to safety.

The 2nd “*” denotes the rated output wattage designation, which can be “01” to “60”, in step of 1 denote 1W.

The 3rd “*” denotes the standard rated output voltage designation, which can be “09”, “15”, “24”, “48”;

The 4th “*” is optional deviation, subtracted from standard output voltage, which can be “-0.01” to “-23.9” with interval of 0.01, or blank to indicate no voltage different.

The 5th “*” =-T2 means desktop class II with C8 AC inlet

=-T2A means desktop class II with C8 AC inlet

=-T3 means desktop class I or class II with functional earth with C14 AC inlet

=-T3A means desktop class I or class II with functional earth with C6 AC inlet

=-F means Open Frame class I or class II with functional earth

=-FW means Open Frame class II

=-P2 means Encapsulated class II

=-P3 means Encapsulated class I or class II with functional earth

The last “*” denote any six character = 0-9 or A-Z or ()[] or – or blank for marketing purposes.

GT*96600-****

The 1st “*” part can be ‘M’ or ‘-’ or ‘H’ for market identification and not related to safety.

The 2nd “*” denotes the rated output wattage designation, which can be “01” to “65”, with interval of 1.

The 3rd “*” denote the standard rated output voltage designation, which can be “05” to “54” or “5.0” to “54.0” in 0.1V increments.

The 4th “*” =-T2 means desktop class II with C8 AC inlet

=-T2A means desktop class II with C18 AC inlet

=-T3 means desktop class I or class II with functional earth with C14 AC inlet

=-T3A means desktop class I or class II with functional earth with C6 AC inlet

=-T2L means desktop class II with C8 AC inlet and housing with a DC jack

=-T2AL means desktop class II with C18 AC inlet and housing with a DC jack

=-T3L means desktop class I or class II with functional earth with C14 AC inlet and housing with a DC jack

=-T3AL means desktop class I or class II with functional earth with C6 AC inlet and housing with a DC jack

=-R2 means hybrid desktop housing class II with C8 AC inlet

=-R3A means hybrid desktop housing class I or class II with functional earth with C6 AC inlet

=-F means Open Frame class I or class II with functional earth

=-FW means Open Frame class II

=-P2 means Encapsulated class II

=-P3 means Encapsulated class I or class II with functional earth

The last “*” denote any six character = 0-9 or A-Z or ()[] or – or blank for marketing purposes.

GT*96600-*56***

The 1st “*” part can be ‘M’ or ‘-’ or ‘H’ for market identification and not related to safety.

The 2nd “*” denotes the rated output wattage designation, which can be “01” to “70”, with interval of 1.

The 3rd “*” =-T2 means desktop class II with C8 AC inlet

=-T2A means desktop class II with C18 AC inlet

=-T3 means desktop class I or class II with functional earth with C14 AC inlet

=-T3A means desktop class I or class II with functional earth with C6 AC inlet

The 4th “*” =-AP or -PP or -SP

-AP (with baby board) stands for Active POE

-PP (no baby board) stands for Passive POE

-SP (no baby board) stands for Simple POE

The last * denote any six character = 0-9 or A-Z or ()[] or – or blank for marketing purposes.

Date: 09 June, 2021

Signature:

