

Certificate



Intertek

for European Product Safety

Reference No. 1707930

ITE Power Supply

Type designation

GT**-*****, GT*96600-*56***

Certificate holder

GlobTek, Inc.
186 Veterans Dr. Northvale, NJ 07647
USA

The product complies with the standard(s)

EN 60950-1:2006+A11:2009+A1:2010+A12:2011+A2:2013

Date of expiry

20 June 2019

EU Directive information

According to the principle of presumption of conformity, this certificate constitutes support for an EC Declaration of Conformity and CE marking according to the Low Voltage Directive 2014/35/EU.


Additional information in Appendix.

Certification Body

Intertek Semko AB, Product Certification

Place Shanghai

Signed



Gary Hu

Date 03 March 2017
Page 1 of 4



Intertek
Appendix

Reference No. 1707930

Technical data

Type designation

Input

Output

BRAND name:

Product information

GT**_****, GT*96600-*56***

GT**_****: Input: 100-240V~, 50-60Hz, 1.5A;

GT*96600-*56***: Input: 100-240V~, 50-60Hz, 2.0A;

GT**_****: Output: 5-54VDC, Max. 60W

GT*96600-*56***: Output: 56VDC, Max. 70W

(See model list for detail)



GT**_****

The 1st "*" part can be 'M' or '-' or 'H' for market identification and not related to safety.

The 2nd "*" can be 91099 or 96600 for market identification

The 3rd "*" denotes the rated output wattage designation, which can be "01" to "60", with interval of 1.

When the 2nd "*" = 91099

The 4th "*" denotes the standard rated output voltage designation, which can be "09", "15", "24", "48";

The 5th "*" is optional deviation, subtracted from standard output voltage, which can be "-0.01" to "-23.9" with interval of 0.01, or blank to indicate no voltage different.

The 4th "*" and 5th "*" together denote the output voltage, with a range of 5-48volts.

When the 2nd "*" = 96600

The 4th "*" denote the standard rated output voltage designation, which can be "05" to "54" or "5.0" to "54.0" in 0.1V increments.

The 5th "*" = Blank

The 6th "*" = -T2 means desktop class II with C8 AC inlet

=-T2A means desktop class II with C18 AC inlet

=-T3 means desktop class I with C14 AC inlet

=-T3A means desktop class I with C6 AC inlet

=-T2L means desktop class II with C8 AC inlet and

housing with a DC jack

=-T2AL means desktop class II with C18 AC inlet

and housing with a DC jack

=-T3L means desktop class I with C14 AC inlet

and housing with a DC jack

=-T3AL means desktop class I with C6 AC inlet

and housing with a DC jack

This Certificate is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this certificate. Only the Client is authorized to permit copying or distribution of this certificate and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.



Intertek Appendix

Reference No. 1707930

=-R2 means hybrid desktop housing class II with C8 AC inlet

=-R3A means hybrid desktop housing class I with C6 AC inlet

=-F means Open Frame class I

=-FW means Open Frame class II

=-P2 means Encapsulated class II

=-P3 means Encapsulated class I

The last * denote any six character = 0-9 or A-Z or ()[] or – or blank for marketing purposes.

GT*96600-*56***

The 1st "*" part can be 'M' or '-' or 'H' for market identification and not related to safety.

The 2nd "*" denotes the rated output wattage designation, which can be "01" to "70", with interval of 1.

The 3rd "*" =-T2 means desktop class II with C8 AC inlet

=-T2A means desktop class II with C18 AC inlet

=-T3 means desktop class I with C14 AC inlet

=-T3A means desktop class I with C6 AC inlet

The 4th "*" =-AP or -PP or -SP

-AP (with baby board) stands for Active POE

-PP (no baby board) stands for Passive POE

-SP (no baby board) stands for Simple POE

The last * denote any six character = 0-9 or A-Z or ()[] or – or blank for marketing purposes.

(Details see attachment.)

Attachment:

Model list:

GT*96600--T2/T2A/T3/T3A/T2L/T2AL/T3L/T3AL* Desktop models**

Model	Output Voltage	Max. output current	Max. output power
GT*96600-**-T2/T2A/T3/T3A/T2L/T2AL/T3L/T3AL*	5-6.7V	8A	40W
GT*96600-**-T2/T2A/T3/T3A/T2L/T2AL/T3L/T3AL*	6.8-54V	6A	60W

This Certificate is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this certificate. Only the Client is authorized to permit copying or distribution of this certificate and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.



Intertek Appendix

Reference No. 1707930

GT*96600-*56-T2/T2A/T3/T3A-AP/PP/SP* Desktop models

GT*96600-*56-T2/T2A/T3/T3A-AP/PP/SP*	56V	1.25A	70W
--------------------------------------	-----	-------	-----

GT*96600-***-R2/R3A* External/Hybrid models

Model	Output Voltage	Max. output current	Max. output power
GT*96600-**-R2/R3A*	5-6.7V	8A	40W
GT*96600-**-R2/R3A*	6.8-54V	6A	60W

GT*91099-***-T2/T2A/T3/T3A/F/FW/P2/P3* External/Hybrid desktop or direct plug-in model or Open Frame or Encapsulated

Model	Output Voltage	Max. output current	Max. output power
GT*91099-*09*-T2/T2A/T3/T3A/F/FW/P2/P3*	5-9V	6A	50W
GT*91099-*15*- T2/T2A/T3/T3A/F/FW/P2/P3*	9.1-15V	6A	60W
GT*91099-*24*- T2/T2A/T3/T3A/F/FW/P2/P3*	15.1-24V	4A	60W
GT*91099-*48*- T2/T2A/T3/T3A/F/FW/P2/P3*	24.1-48V	2.5A	60W

Note: For 91099 series, T2A model use C8 inlet.

Manufacturing site(s) GlobTek (Suzhou) Co., Ltd
Building 4, No. 76, Jin Ling East Rd., Suzhou Industrial Park, Suzhou,
Jiangsu 215121, P.R.China


Safety related parts of the user instructions shall be written in a language acceptable to the country where the product is to be used.

If the product is to be marketed in different European countries, it must be provided with a certified plug appropriate for each country.

According to the principle of presumption of conformity, this certificate, which includes production control, constitutes support for an EC Declaration of Conformity and CE marking according to the Low Voltage Directive 2014/35/EU.

This presumption can expire before end of validity of this certificate due to new issued Standard or Amendment and changes within the EU legislation.

Certification Body Intertek Semko AB, Product Certification *Place* Shanghai

Signed 
Gary Hu *Date* 03 March 2017

This Certificate is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this certificate. Only the Client is authorized to permit copying or distribution of this certificate and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.