

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

ITE Power Supply

Name and address of the applicant

GlobTek, Inc.
186 Veterans Drive Northvale, NJ 07647, USA

Name and address of the manufacturer

GlobTek, Inc.
186 Veterans Drive Northvale, NJ 07647, USA

Name and address of the factory


See page 2

Note: When more than one factory, please report on page 2☒ Additional Information on page 2

Ratings and principal characteristics

See page 2

Trademark (if any)

 **GlobTek, Inc.**

Customer's Testing Facility (CTF) Stage used

/

Model / Type Ref.

GTA41077PWWWWV-X.X

Additional information (if necessary may also be reported on page 2)

Unit also complies with EN 60950-1:2006 + A1:2010 + A2:2013 + A11:2009 + A12:2011

☒ Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 60950-1:2005 + A1:2009 + A2:2013

As shown in the Test Report Ref. No. which forms part of this Certificate

T223-0258/19, dated 2019-06-19


This CB Test Certificate is issued by the National Certification Body

SIQ Ljubljana, Tržaška cesta 2, SI-1000 Ljubljana, Slovenia
T +386 1 4778 100, F +386 1 4778 444, info@siq.si, www.siq.si

SIQ Ljubljana is accredited by Slovenian Accreditation with accreditation number CP-001 in the field of certification of products, processes and services.

Date: 2019-06-19

Signature: Bojan Pečavar



Name and address of the factories:

1) GlobTek, Inc.,
186 Veterans DR, Northvale, NJ 07647, USA

2) GlobTek (Suzhou) Co. Ltd.,
Building 4, # 76, Jin Ling East Rd., Suzhou Park, Suzhou, Jiangsu 215021, P.R.China

Model/Type reference:

GTA41077PWWWWV-X.X

WWW is output power in Watts, offset by 1 decimal place to the right. Max. Watt 120;

VV is output voltage for base model;

-X.X is optional for specifying the output voltage deviation in 0.1 increments and X.X is to be subtracted from the base rated voltage or can be blank.

Ratings and principal characteristics:

Input: 100-240 Vac; 1,8 A; 50-60 Hz

Output: 12 - 48 Vdc; max. 8,33 A (see below table for details):

Model	Output Voltage	Output Current	Max. Watt
GTA41077PWWWW12	12 Vdc	0 – 8.33 A	99.96 W
GTA41077PWWWW15-X.X	12.1 – 15 Vdc	0 – 8.28 A	99.96 W
GTA41077PWWWW19-X.X	15.1 – 19 Vdc	0 – 7.95 A	120 W
GTA41077PWWWW24-X.X	19.1 – 24 Vdc	0 – 6.28 A	120 W
GTA41077PWWWW36-X.X	24.1 – 36 Vdc	0 – 4.98 A	120 W
GTA41077PWWWW48-X.X	36.1 – 48 Vdc	0 – 3.32 A	120 W

Additional information (if necessary)

This CB test certificate substitutes previously issued CB test certificate No. SI-3173, dated 2012-01-31, due to update of test report.

Date: 2019-06-19

Signature: Bojan Pečavar

