

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Direct Plug-in or Open frame Power Supply

Name and address of the applicant

GlobTek, Inc.
186 Veterans Drive Northvale, NJ 07647, USA

Name and address of the manufacturer

GlobTek, Inc.
186 Veterans Drive Northvale, NJ 07647, USA

Name and address of the factory


GlobTek, Inc.
186 Veterans Drive Northvale, NJ 07647, USA*Note: When more than one factory, please report on page 2*

Ratings and principal characteristics

☒ Additional Information on page 2

See page 2.

Trademark

 **GlobTek, Inc.**

Customer's Testing Facility (CTF) Stage used

/

Model / Type Ref.

GT (M or -) 41060 (- or CC) WWWV-X.XA-FW Family
(See page 2 for details).Additional information (if necessary may also
be reported on page 2)This CB test certificate substitutes previously issued CB
test certificate No. SI-5865, dated 2017-02-14, due to
update of test report.☐ Additional Information on page 2A sample of the product was tested and found
to be in conformity with

IEC 60601-1:2005 + A1:2012

As shown in the Test Report Ref. No. which
forms part of this Certificate


T223-0541/19, issued on 2019-09-12

This CB Test Certificate is issued by the National Certification Body

SIQ Ljubljana, Tržaška cesta 2, SI-1000 Ljubljana, Slovenia
T +386 1 4778 100, F +386 1 4778 444, info@siq.si, www.siq.siSIQ Ljubljana is accredited by Slovenian Accreditation with accreditation number CP-001 in the
field of certification of products, processes and services.

Date: 2019-09-12

Signature: Bojan Pečavar



Model/type reference:

GT (M or -) 41060 (- or CC) WWVV-X.XA-FW Family where:

M or - for marked identification and not related to safety

41060: Series code

(- or CC): "-" = Constant Voltage Model, CC = Constant Current Model

WW: is the rated output wattage designation, with a maximum value of "25"

VV: is the standard rated output voltage designation, with a maximum value of "30"

- X.X: Denotes the optional deviation, subtracted or added from standard output voltage in 0,1 volt increments or blank to indicate the no voltage different.

A is optional for marked identification and not related to safety.

- FW: is optional and means open frame power supply

Models providing MOPP protection are additionally marked with 2MOPP near model name.

Name and address of the factories:

1) GlobTek Inc.,

186 Veterans Drive Northvale, NJ 07647, USA

2) GlobTek (Suzhou) Co., Ltd.

Building 4, No. 76, Jinling East Road, Suzhou Industrial Park, Jiangsu CN-215021, China

Ratings and principal characteristics:

I/P: 100-240 V~; 50-60 Hz; 0,6 A; Class II

O/P: 5-30 Vdc; Max. 3,0 A; Max. 25 W:

Additional information (if necessary)

Date: 2019-09-12

Signature: Bojan Pečavar



Model name	Output voltage	Output current	Max. Output power
GTM41060(- or CC)-1505A / GTM41060(- or CC)-1505A-FW	5,0 Vdc	3,0 A	15 W
GTM41060(- or CC)-1706-X.XA / GTM41060(- or CC)-1706-X.XA-FW	5,1-6 Vdc	3,0 A	18 W
GTM41060(- or CC)-1807-X.XA / GTM41060(- or CC)-1807-X.XA-FW	6,1-7 Vdc	2,95 A	18 W
GTM41060(- or CC)-1809-X.XA / GTM41060(- or CC)-1809-X.XA-FW	7,1-9 Vdc	2,54 A	18 W
GTM41060(- or CC)-2512-X.XA / GTM41060(- or CC)-2512-X.XA-FW	9,1-12 Vdc	2,75 A	25 W
GTM41060(- or CC)-2515-X.XA / GTM41060(- or CC)-2515-X.XA-FW	12,1-15 Vdc	2,07 A	25 W
GTM41060(- or CC)-2518-X.XA / GTM41060(- or CC)-2518-X.XA-FW	15,1-18 Vdc	1,66 A	25 W
GTM41060(- or CC)-2520-X.XA / GTM41060(- or CC)-2520-X.XA-FW	18,1-20 Vdc	1,38 A	25 W
GTM41060(- or CC)-2524-X.XA / GTM41060(- or CC)-2524-X.XA-FW	20,1-24 Vdc	1,24 A	25 W
GTM41060(- or CC)-2530-X.XA / GTM41060(- or CC)-2530-X.XA-FW	24,1-30 Vdc	1,04 A	25 W

Additional information (if necessary)

Date: 2019-09-12

Signature: Bojan Pečavar

Bj