Ref. Certif. No

NO131210

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	ICT/ITE Power Supply
Name and address of the applicant	GlobTek, Inc. 186 Veterans Drive Northvale NJ 07647 United States of America
Name and address of the manufacturer	GlobTek, Inc. 186 Veterans Drive Northvale NJ 07647 United States of America
Name and address of the factory	See next page(s)
Note: *When more than one factory,please report on page 2*	☑ Additional Information on Page 2
Ratings and Principal characteristics	Input: 0.6A 100-240V~ 50-60Hz Output: 5-30Vdc, Max. 3.6A, Max. 18W Cl.II
Trademark /Brand (If any)	GlobTek, Inc.
Customer's Testing Facility (CTF) Stage used	
Model/Type Ref	GT*41061-***
Additional information(If necessary may also be reported on Page 2)	☑ Additional Information on Page 2
A sample of the product was tested and found to be in conformity with	IEC 62368-1:2018
As shown in the Test Report Ref. No. which forms part of this Certificate	REP040637

This CB Test Certificate is issued by the National Certification Body

Nemko

Philip Pedersen vei 11,
NO-1366 Lysaker, Norway
Date: 21-06-2024

Jiyea Gim

Signature: Jiyea Gim
Certification department

Disclaimer: This document is controlled and has been released electronically.
Only the version on the IECEE Website is the current document version

Ref. Certif. No

NO131210

GlobTek, Inc.
186 Veterans Drive
Northvale NJ 07647
United States of America

GlobTek (Suzhou) Co., Ltd
Building 4, No. 76, Jin Ling East Rd., Suzhou Industrial Park, Suzhou,JiangSu 215021
China

Additional Information (if necessary)

The 1st '*' part can be 'M' or '-' or 'H' for market identification and not related to safety.
The 2nd '*' part denotes the rated output wattage designation, which can be '01' to '18', with interval of 1.
The 3rd '*' part denotes the standard rated output voltage designation, which can be '12' '18', '24' or '30'.
The 4th '*' part is optional, which can be '-0.1' to '-7.0' with interval of 0.1 to denote voltage deviation or blank to indicate no voltage different. The result by subtracting the deviation value from the standard rated output voltage denotes the rated output voltage, with a range of 5 - 30 volts. The standard rated output voltage is separately 12V, 18V, 24V and 30V.

Nemko

Philip Pedersen vei 11,
NO-1366 Lysaker, Norway
Date: 21-06-2024

Jiyea Gim

Signature: Jiyea Gim
Certification department

Disclaimer: This document is controlled and has been released electronically.
Only the version on the IECEE Website is the current document version