本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO.: 2014010907721524

NAME AND ADDRESS OF THE APPLICANT

GlobTek,Inc.

186 Veterans Dr. Northvale, NJ 07647 / USA

NAME AND ADDRESS OF THE MANUFACTURER

GlobTek,Inc.

186 Veterans Dr. Northvale, NJ 07647 / USA

NAME AND LOCATION OF THE FACTORY

GlobTek (Suzhou) Co., Ltd

Building 4, No. 76 JinLing East Road,Suzhou Industrial Park, Suzhou, JiangSu, 215021, China.

PRODUCT NAME,MODEL AND SPECIFICATION

ITE POWER SUPPLY

See Appendix ，Altitude up to 2000m

STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS

GB 17625.1-2022（Class A）;GB 4943.1-2022;GB/T 9254.1-2021

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification(REFNO. CNCA-C09-01:2023).

Valid from: Jul.04,2024 **Valid until:** Oct.24,2027

Date of original issued: Sep.12,2014

The certificate information and validity could be checked by scanning the QR code below or logging in to the website of the issuing authority, or on the website of the CNCA (www.cnca.gov.cn).

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P

SIGNATURE: 谢肇煦

中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.

本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2014010907721524

Appendix: Page 1 of 1

GT*41061-***（The 1st '*' part can be 'M' or '-' or 'H' for market identification; The 2nd '*' part denotes the rated output wattage designation, which can be "01" to "18", with interval of 1; The 3rd '*' part denotes the standard rated output voltage designation, which can be "12", "18", "24" or "30"; The 4th '*' part is optional, which can be "-0.1" to "-7.0" with interval of 0.1, the 3rd and 4th '*' together denotes the rated output voltage, with a range of 5 - 30 volts. When output voltage is 12V, 18V, 24V and 30V, the 4th '*' is blank.）;
Input: 100-240V～, 50-60Hz, 0.6A;
Detail see below Table

Modek	Output voltage（V）	Max. rated output current（A）	Max. rated output power（W）
GT*41061-*12*	5-12Vdc	3.6A	18W
GT*41061-*18*	12.1-18Vdc	1.49A	18W
GT*41061-*24*	18.1-24Vdc	1.0A	18W
GT*41061-*30*	24.1-30Vdc	0.75A	18W

This page is attached to the certificate and should be used at the same time as the certificate page.