



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO.: 2014010907674784

Valid from: Dec.29,2023

Valid until: Nov.08,2027

**NAME AND REGISTERED
ADDRESS OF THE APPLICANT**

GlobTek,Inc.
186 Veterans Dr. Northvale, NJ 07647 / USA

**NAME AND REGISTERED
ADDRESS OF THE
MANUFACTURER**

GlobTek,Inc.
186 Veterans Dr. Northvale, NJ 07647 / USA

**NAME AND LOCATION
OF THE FACTORY**

GlobTek (Suzhou) Co., Ltd
Building 4, No. 76 JinLing East Road,Suzhou Industrial Park, Suzhou, JiangSu, 215021, China.

PRODUCT MODEL(S)

Power Supply
See appendix(Altitude up to 2000m)

**STANDARDS AND
TECHNICAL REQUIREMENTS**

GB 17625.1-2022 (Class A) ;GB 4943.1-2022;GB/T 9254.1-2021

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification(REFNO. CNCA-C09-01:2023)

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

Date of original issued: Feb.24,2014

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P

The certificate information is available through the QR code below or CNCA's website: www.cnca.gov.cn



SIGNATURE:

谢肇煦



CHINA QUALITY CERTIFICATION CENTRE



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2014010907674784

page 1 of 2

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

GT*41076-****

The 1st “*” denotes “M” or “-” or “H” for market identification and not related to safety.

The 2nd “*” denotes the rated output wattage designation, which can be “01” to “06”, with interval of 1.

The 3rd “*” denotes the standard rated output voltage designation, which can be

“05”, “06”, “07”, “09”, “12”, “15”, “18”, “20”, “24” or “30” ;

The 4th “*” is optional deviation, subtracted from standard output voltage, which can be “-0.1” to “-5.9” with interval of 0.1, or blank to indicate no voltage different.

The last * denote any six characters, which can be 0-9 or A-Z or [] or – or blank for marketing purposes.

Input : 100-240VAC , 50-60Hz , 0.16-0.1A

The s and outputs are shown in the table below

Model	Input ratings	Output voltage	Max.output current	Max.output power
GT*41076-*05*	100-240Vac 50-60Hz 0.16-0.1A	5Vdc	1.2A	6W
GT*41076-*06**	100-240Vac 50-60Hz 0.16-0.1A	5.1-6Vdc	1.17A	6W
GT*41076-*07**	100-240Vac 50-60Hz 0.16-0.1A	6.1-7Vdc	0.98A	6W
GT*41076-*09**	100-240Vac 50-60Hz 0.16-0.1A	7.1-9Vdc	0.84A	6W
GT*41076-*12**	100-240Vac 50-60Hz 0.16-0.1A	9.1-12Vdc	0.65A	6W
GT*41076-*15**	100-240Vac 50-60Hz 0.16-0.1A	12.1-15Vdc	0.49A	6W
GT*41076-*18**	100-240Vac 50-60Hz 0.16-0.1A	15.1-18Vdc	0.39A	6W
GT*41076-*20**	100-240Vac 50-60Hz 0.16-0.1A	18.1-20Vdc	0.33A	6W



CHINA QUALITY CERTIFICATION CENTRE



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2014010907674784

page2of 2

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

GT*41076-*24**	100-240Vac 50-60Hz 0.16-0.1A	20.1-24Vdc	0.29A	6W
GT*41076-*30**	100-240Vac 50-60Hz 0.16-0.1A	24.1-30Vdc	0.24A	6W



CHINA QUALITY CERTIFICATION CENTRE