

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Direct plug in ac/dc adaptor with exchangeable plugs

Name and address of the applicant

GlobTek Inc.
186 Veterans Dr Northvale, NJ 07647 / USA

Name and address of the manufacturer

GlobTek Inc.
186 Veterans Dr Northvale, NJ 07647 / USA

Name and address of the factory

See page 2

Note: When more than one factory, please report on page 2☒ Additional Information on page 2

Ratings and principal characteristics

See page 2

Trademark (if any)

 **GlobTek, Inc.**

Customer's Testing Facility (CTF) Stage used

/

Model / Type Ref.

See page 2

Additional information (if necessary may also be reported on page 2)

Unit also complies with EN 60950-1:2006 + A1:2010 + A2:2013 + A11:2009 + A12:2011

☒ Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 60950-1:2005 (2nd Ed.) + A1:2009 + A2:2013

As shown in the Test Report Ref. No. which forms part of this Certificate

T223-0584/18, dated 2018-12-17


This CB Test Certificate is issued by the National Certification Body

SIQ Ljubljana, Tržaška cesta 2, SI-1000 Ljubljana, Slovenia
T +386 1 4778 100, F +386 1 4778 444, info@siq.si, www.siq.si

SIQ Ljubljana is accredited by Slovenian Accreditation with accreditation number CP-001 in the field of certification of products, processes and services.

Date: 2018-12-17

Signature: Bojan Pečavar



Name and address of the factories:

GlobTek, Inc.
186 Veterans Drive Northvale,
NJ 07647, USA

GlobTek (Suzhou) Co., Ltd
Building 4, No. 76, Jinling East Road,
Suzhou Industrial Park, Jiangsu 215021, China

Model/Type reference:

GTM41076-WWVV-X.X

Nomenclature:

41076 denotes series code

WW denotes rated power

VV denotes rated output voltage between 5 Vdc and 30 Vdc.

-X.X is optional or blank and denotes voltage differentiator (subtracting X.X Volts from standard output voltage in 0,1 V increments).

Ratings and principal characteristics:

Model Name:	Input ratings:	Output ratings:
GTM41076-0605	100-240 Vac; 50-60 Hz; 160-100 mA	5,0 Vd.c.; 1,2 A
GTM41076-0606-X.X	100-240 Vac; 50-60 Hz; 160-100 mA	6,0 Vd.c.; 1,0 A
GTM41076-0607-X.X	100-240 Vac; 50-60 Hz; 160-100 mA	7,0 Vd.c.; 0,85 A
GTM41076-0609-X.X	100-240 Vac; 50-60 Hz; 160-100 mA	9,0 Vd.c.; 0,66 A
GTM41076-0612-X.X	100-240 Vac; 50-60 Hz; 160-100 mA	12,0 Vd.c.; 0,5 A
GTM41076-0615-X.X	100-240 Vac; 50-60 Hz; 160-100 mA	15,0 Vd.c.; 0,4 A
GTM41076-0618-X.X	100-240 Vac; 50-60 Hz; 160-100 mA	18,0 Vd.c.; 0,33 A
GTM41076-0620-X.X	100-240 Vac; 50-60 Hz; 160-100 mA	20,0 Vd.c.; 0,3 A
GTM41076-0624-X.X	100-240 Vac; 50-60 Hz; 160-100 mA	24,0 Vd.c.; 0,25 A
GTM41076-0630-X.X	100-240 Vac; 50-60 Hz; 160-100 mA	30,0 Vd.c.; 0,16 A

Additional information (if necessary)

This CB test certificate substitutes previously issued CB test certificate No. SI-6822, dated 2018-10-16, due to update of test report.

Date: 2018-12-17

Signature: Bojan Pečavar

