

Poročilo o preskusu / Test Report

Št. / No.:

T211-0686R/12

Datum / Date:

2013-01-08

Proizvod / Product	Listov / Pages
Power supply Model: GT-41052-1548 GT-41080, GT-41081, GTM41076, GTM41134, GT-43007, GT-41062, GT-41135, GTM41080, GTM41081	6
Naročnik / Applicant	Vrsta preskusa / Test procedure
GlobTek, Inc 186 Veterans Dr, Northvale, NJ 07647 / USA	IP52
Proizvajalec / Manufacturer	Št. Merjencev / No. of Items tested
GlobTek, Inc 186 Veterans Dr, Northvale, NJ 07647 / USA	1
Blagovna znamka / Trade Mark	Mapa predmeta št. / Subject File No.
GlobTek	C20121557
Standardi – predpisi / Standards - regulations	Kraj preskusa / Place of test
IEC 60529:2001	SIQ - Slovenian Institute of Quality and Metrology, Tržaška 2, 1000 Ljubljana, Slovenia
	Opomba / Remark
	/

Zaključek / Conclusion

Tested product complies with the requirements of stated standards for protection degree IP 52.

The test results relate only to the items tested.

Date of receipt of test items: 2012-11-08

Date of performance of tests: 2012-11-12 to 2012-11-14

The report T212-0686R/12 supersedes the report T212-0686/12 due to added models name GTM41080 and GTM41081.

Testni laboratorij je akreditiran pri Slovenski akreditaciji, reg.št.:LP-009 /
Testing Laboratory is accredited by Slovenian Accreditation, Reg. No. LP-009

Odgovoren za preskušanje / Responsible for the test

Vodja področja / Department Manager

Mirko Čoko

dr. Miha Otrin

Slovenski institut za kakovost in meroslovje • Slovenian Institute of Quality and Metrology
Tržaška cesta 2, SI-1000 Ljubljana, Slovenia • t: +386 1 4778 100 • f: +386 1 4778 444 • e: info@siq.si • http://www.siq.si
Razmnoževanje poročila, razen v celoti, ni dovoljeno / This report shall not be reproduced except in full

1 TEST EQUIPMENT

- Rigid test wire diameter of 1 mm as specified by the standard (2013-01-22),
- Test device for verification of protection against vertically falling water drops-drip box-SIQ,
- Digital protractor MITUTOYO; Model: PRO 360 (2013-01-27)

Note: The date of the recommended recalibration is given for each measuring instrument (in brackets).

2 EQUIPMENT UNDER TEST (EUT)

Power supply, model GT-41052-1548 was subjected to testing for IP52 degree of protection (Figure 1). Models GT-41080, GT-41081, GTM41076, GTM41134, GT-43007, GT-41062, GT-41135, GTM41080 and GTM41081 have the same enclosure as GT-41052.



Figure 1

IP52 numeric description:

The first characteristic numeral X indicates the degree of protection against solid foreign objects (degree 5-dust protected). The protection is satisfactory if talcum powder has not accumulated in a quantity or location such that, as with any other kind of dust, it could interfere with the correct operation of the equipment or impair safety.

The second characteristic numeral Y indicates the degree of protection provided by enclosures with respect to harmful effects on the equipment due to the ingress of water (degree 2-protected against dripping water). If any water has entered shall have no harmful effects.

3 TEST CONDITIONS

During the testing the power supply was connected to the socket outlet, see Figure 2. The plug part (Figure 3) with the socket outlet was not subject of the test. Test results do not relate to the whole power supply but only to the enclosure (without the plug part).



Figure 2: sample unit

Socket
outlet



Figure 3: sample unit

Plug part

3.1 Dust test-IP5Y (IEC 60529, tables 2 and 7, sub-cl. 13.4; 13.5)

- Test chamber-as specified in standard,
- Dust, used for the test: talcum powder,
- Environmental temperature 24⁰C,
- No under pressure inside the enclosure,
- Duration of the exposure: 8 hours




Figure 4: EUT before the dust test



Figure 5: EUT after the dust test

3.2 Tests for protection against ingress of water-IPX2 (IEC 60529, tables 3 and 8, sub-cl. 14.2.2)

- Test device, drip box-as specified in standard,
- Water flow rate: 3 mm/min,
- The position of the test sample was fixed on 15⁰ on either side of the vertical in two mutually perpendicular planes,
- The test sample was tested for 2.5 minutes in each of four fixed positions (Figures 6 to 9),
- The total duration of the exposure was 10 minutes



Figure 6



Figure 7



Figure 8



Figure 9

3.3 Electric strength test

Immediately following the water test the dielectric strength test with 4000 V a.c. has been conducted between primary and secondary terminals and between primary terminals and enclosure. The voltage was applied and maintained for a period of one minute between the points indicated. There was no break down.

Conclusion: After the tests the enclosure was opened. There was no dust and no water inside the enclosure (Figures 10 and 11).



Figure 10



Figure 11

4 CONCLUSIONS

After the exposure was concluded, the visual examination of the sample was performed. Results were obtained as follows:

- There was no dust and no water inside the enclosure.
- There was no break down during the dielectric strength test.

Result: Following the acceptance conditions, the equipment under test sustained the test conditions for IP52 degree of protection. The test results relate to the enclosure of the power supply without the plug part.