

IEC**IECEE**
CB
SCHEME

Ref. Certif. No.

SE-75810IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST
CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEMESYSTEME CEI D'ACCEPTATION MUTUELLE DE
CERTIFICATS D'ESSAIS DES EQUIPEMENTS
ELECTRIQUES (IECEE) METHODE OC**CB TEST CERTIFICATE****CERTIFICAT D'ESSAI OC**Product
Produit

ITE Power Supply

Name and address of the applicant
Nom et adresse du demandeurGlobTek, Inc.
186 Veterans Dr. Northvale, NJ 07647,
USAName and address of the manufacturer
Nom et adresse du fabricant

Same as above

Name and address of the factory
Nom et adresse de l'usine
Note: When more than one factory, please report on page 2
Note: Lorsque il y plus d'une usine, veuillez utiliser la 2^{ème} page

See page 2

Ratings and principal characteristics
Valeurs nominales et caractéristiques principalesInput: 100-240V~, 50-60Hz, 2.0A
Output: See page 2Trademark (if any)
Marque de fabrique (si elle existe)

GlobTek

Type of Manufacturer's Testing Laboratories used
Type de programme du laboratoire d'essais
constructeur

-

Model / Type Ref.
Ref. De type

GT*43004P-***-**

Additional information (if necessary may also be
reported on page 2)
Les informations complémentaires (si nécessaire,
peuvent être indiqués sur la 2^{ème} page)

See page 2

A sample of the product was tested and found
to be in conformity with
Un échantillon de ce produit a été essayé et a été
considéré conforme à laIEC 60950-1:2005+A1. Group and national differences for the
CENELEC countries (EN 60950-1:2006+A11+A1+A12)As shown in the Test Report Ref. No. which forms part
of this Certificate
Comme indiqué dans le Rapport d'essais numéro de
référence qui constitue partie de ce Certificat

140200043SHA-001

This CB Test Certificate is issued by the National Certification Body
Ce Certificat d'essai OC est établi par l'Organisme **National de Certification**Intertek Semko AB
Box 1103
SE-164 22 Kista, Sweden
Int +46 8 750 00 00

Date: 3 April 2014

Intertek

Signature:

Gary Hu

**Factories
Les usines**

GlobTek, Inc.
186 Veterans Dr. Northvale, NJ 07647 USA

GlobTek (Suzhou) Co., Ltd
Building 4, No. 76, Jin Ling East Rd., Suzhou Industrial Park, Suzhou, JiangSu 215021, China

**Additional information (if necessary)
Information complémentaire (si nécessaire)**

The national differences for AU, CA, CN, JP, KR, SG and US have been checked.

Explanation for model GT*43004P-***-**:

The 1st "*" part can be 'M' or '-' or 'H' for market identification and not related to safety.

The 2nd "*" part denotes the rated output wattage designation, which can be "01" to "120", with interval of 1.

The 3rd "*" part denotes the standard rated output voltage designation, which can be "8.9", "16", "24", "35" and "48". Each standard rated output voltage designation corresponds to a transformer model. Each transformer model is identical in insulation construction including clearance and creepage except number of turns per coil.

The 4th "*" part is optional, which can be "-0.1" to "-12.9" with interval of 0.1 to denote voltage deviation or blank to indicate no voltage different. The result by subtracting the deviation value from the standard rated output voltage denotes the rated output voltage, with a range of 5-48 volts.

The 5th "*" part can be 'F' to denote open frame power supply model or 'T' to denote power adapter model.

The 6th "*" part can be '2' to denote Class II model, or '3' or '3A' to denote two types of Class I models with different appliance inlets when the 5th "*" part is 'T'. Otherwise, the 6th "*" part is blank when the 5th "*" part is 'F'.

Tests were performed on 5Vdc/10A output and 48Vdc/2.5A output power adapter model as worst condition, and also performed on other output models for reference. For open frame model, temperature testing, leakage current test and mechanical strength test shall be performed on this component when installed in the end product.

Model list:

Model	Rated output voltage range	Max. rated output current	Max. rated output power	Transformer model
GT*43004P-*8.9*-**	5-8.9Vdc	10A	90W	XF00828
GT*43004P-*16*-**	9-16Vdc	10A	120W	XF00870
GT*43004P-*24*-**	16.1-24Vdc	7.45A	120W	XF00849
GT*43004P-*35*-**	24.1-35Vdc	5A	120W	XF00854
GT*43004P-*48*-**	35.1-48Vdc	3.42A	120W	XF00830

Date: 3 April 2014

Signature: 