本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO.: 2020010907290044

NAME AND ADDRESS OF THE APPLICANT

GlobTek,Inc.

186 Veterans Dr. Northvale, NJ 07647， USA

NAME AND ADDRESS OF THE MANUFACTURER

GlobTek,Inc.

186 Veterans Dr. Northvale, NJ 07647， USA

NAME AND LOCATION OF THE FACTORY

GlobTek (Suzhou) Co., Ltd

Building 4, No. 76 JinLing East Road,Suzhou Industrial Park, Suzhou, JiangSu, 215021, China.

PRODUCT NAME,MODEL AND SPECIFICATION

Power supply

See Appendix(Altitude up to 5000m)

STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS

GB 17625.1-2022(Class A);GB 4943.1-2022;GB/T 9254.1-2021

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification(REFNO. CNCA-C09-01:2023).

Valid from: Jan.29,2024 **Valid until:** Apr.26,2025

Date of original issued: Apr.26,2020

The certificate information and validity could be checked by scanning the QR code below or logging in to the website of the issuing authority, or on the website of the CNCA (www.cnca.gov.cn).

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P

SIGNATURE: 谢肇煦

中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE

本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2020010907290044

Appendix: Page 1 of 1

GT*43007-****-FW (第一个“*”可以为“M” or “-”or“H”代表不同的市场目的，不影响安全和电磁兼容性能；第二个“*”可以为 A=2x3, B=2x4, C=3x5，代表不同的 PCB 尺寸；第三个“*”可以为“01”到“60”，代表额定输出功率，步进为 1W；第四个“*”可以为“05”，“07”，“09”，“12”，“15”，“18”，“24”，“36”，“48”；第五个“*”可以为空白或者“-0.1”到“-11.9”，步进为 0.1；第四个“*”和第五个“*”的差值代表输出电压，范围值为：5-48VDC)

输入 100-240VAC, 50-60Hz, 1.5A.；输出: 5-48VDC, 60W max.

输出规格见下表：

型号	直流输出电压	最大输出电流	最大输出功率
GT*43007-**05*-FW	5VDC	6.0A	30W
GT*43007-**07*-FW	5.1-7VDC	6.0A	30W
GT*43007-**09*-FW	7.1-9VDC	5.0A	45W
GT*43007-**12*-FW	9.1-12VDC	5.0A	60W
GT*43007-**15*-FW	12.1-15VDC	5.0A	60W
GT*43007-**18*-FW	15.1-18VDC	4.0A	60W
GT*43007-**24*-FW	18.1-24VDC	3.31A	60W
GT*43007-**36*-FW	24.1-36VDC	2.50A	60W
GT*43007-**48*-FW	36.1-48 VDC	1.66A	60W

This page is attached to the certificate and should be used at the same time as the certificate page.