



Ref. Certif. No.

SE-81207M1

**IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR
ELECTRICAL EQUIPMENT (IECEE) CB SCHEME**

CB TEST CERTIFICATE

Product

ITE Power supply

Name and address of the applicant

GlobTek, Inc.
186 Veterans Drive Northvale, NJ 07647, USA

Name and address of the manufacturer

Same as applicant

Name and address of the factory


Note: When more than one factory, please report on page 2

See page 2

Ratings and principal characteristics

Input: 100-240V~, 50-60Hz, 0.3A;
Output: 5-5.5VDC, Max 13W

Trademark (if any)



Customer's Testing Facility (CTF) Stage used

-

Model / Type Ref.

GT*46101-***-USB

Additional information (if necessary may also be
reported on page 2)

See page 2

A sample of the product was tested and found
to be in conformity with

IEC 60950-1:2005+A1+A2

As shown in the Test Report Ref. No. which forms part
of this Certificate

150701371SHA-001, 150701371SHA-001 M1

This CB Test Certificate is issued by the National Certification Body

Intertek Semko AB
Box 1103
SE-164 22 Kista, Sweden
Int +46 8 750 00 00

Date: 22 September 2017

Intertek

Signature:


Gary Hu



Ref. Certif. No.

SE-81207M1

Factories

GlobTek, Inc.
186 Veterans Drive Northvale, NJ 07647, USA

GlobTek (Suzhou) Co., Ltd.
Building 4, No.76 JinLing East Road Suzhou Industrial Park
Suzhou JiangSu, 215021, China

Additional information (if necessary)

This certificate replaces CB certificate SE-81207, dated 13 November, 2015. A new certificate has been issued due to updated the national differences for Singapore, Japan, Australia and New Zealand

Group differences for CENELEC countries and national differences for Singapore, Japan, China, Australia/New Zealand, Korea, USA and Canada are considered.

Explanation of type designation GT*46101-***-USB:

The 1st symbol "*" can be "M" or "-" or "H" for market identification and not related to safety.

The 2nd symbol "*" denote the rated output wattage designation, which can be "01" to "13", with interval of 1.

The 3rd symbol "*" denote the standard rated output voltage designation, which can be "05", "06",

The 4th symbol "*" is optional deviation, subtracted from standard output voltage, which can be "-0.5" to "-0.9" with interval of 0.1, or blank to indicate no voltage different.

The 3rd and 4th symbols "***" together denote the output voltage, with a range of 5-5.5 volts.

Model	Rated output voltage range	Max. rated output current	Max. rated output power
GT*46101-*05*-USB	5	2A	10W
GT*46101-*06*-USB	5.1-5.5V	2.54A	13W

Date: 22 September 2017

Signature: