Ref. Certif. No.

SE-95156

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	I.T.E. POWER SUPPLY
Name and address of the applicant	GlobTek, Inc. 186 Veterans Dr. Northvale, NJ 07647, USA
Name and address of the manufacturer	Same as applicant
Name and address of the factory Note: *When more than one factory, please report on page 2*	See page 2
Ratings and principal characteristics	Input: 100-240 V~, 50-60 Hz, 0.45 A; Output: 5-5.5 Vdc, Max. 3.2 A, Max 16 W Class II
Trademark (if any)	GlobTek, Inc.
Customer's Testing Facility (CTF) Stage used	--
Model / Type Ref.	GT*46161-**-*
Additional information (if necessary may also be reported on page 2)	See page 2
A sample of the product was tested and found to be in conformity with	IEC 60950-1:2005+A1+A2
As shown in the Test Report Ref. No. which forms part of this Certificate	190700259TWN-001

This CB Test Certificate is issued by the National Certification Body

Intertek Semko AB
Box 1103
SE-164 22 Kista, Sweden
Int +46 8 750 00 00

Date: 20 August 2019

intertek

Signature:

Ike Wang

Factories

1. GlobTek (Suzhou) Co., Ltd.
   Building 4, No. 76 JinLing East Road, Suzhou Industrial Park, Suzhou, JiangSu, 215021, China
2. GlobTek, Inc.
   186 Veterans Dr. Northvale, NJ 07647, USA

Additional information (if necessary)

The national differences for AU, CA, CN, IL, JP, KR, US and SG have been checked.
The product has also been checked according to EN 60950-1:2006+A11+A1+A12+A2

Explanation for model GT*46161-**-*:
The 1st symbol "*" denotes "M" or "-" or "H" for market identification and not related to safety.
The 2nd symbol "*" denotes the rated output wattage designation, which can be "01" to "16", with interval of 1.
The 3rd symbol "*" denotes the standard rated output voltage designation, which can be "5.0" to "5.5" or "05" to "05.5" with interval of 0.1 Vdc.
The last symbol "*" denotes -USB means Type 1 USB*1, -USB1A means Type 2 USB*1, -USB2A means Type 2 USB*2 and -USBC means Type 2 USB Type C.

Model	Input	Output Voltage	Max. output current	Max. output power
GT*46161-*5.0-*, GT*46161-*05-*	100-240 V~, 50-60 Hz, 0.45 A	5 Vdc	3.2 A	16 W
GT*46161-**-* (The 3rd "*" can be "5.1" to "5.5" or "05.1" to"05.5")		5.1-5.5 Vdc	3.14 A	16 W

All models are similar except for output type and different output voltage.

Date: 20 August 2019

Signature: