



Ref. Certif. No.

SE-88421

**IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR
ELECTRICAL EQUIPMENT (IECEE) CB SCHEME**

CB TEST CERTIFICATE

Product

ITE Power supply

Name and address of the applicant

GlobTek, Inc.
186 Veterans Drive, Northvale, NJ 07647, USA

Name and address of the manufacturer

Same as applicant

Name and address of the factory

Note: When more than one factory, please report on page 2

See page 2

Ratings and principal characteristics

Input: 100-240VAC, 50-60Hz, 0.45A
Output: 5.0-5.5VDC, Max. 3.2A, Max. 16W

Trademark (if any)



Customer's Testing Facility (CTF) Stage used

-

Model / Type Ref.

GT*46161-**-USB

Additional information (if necessary may also be
reported on page 2)

See page 2

A sample of the product was tested and found
to be in conformity with

IEC 60950-1:2005+A1+A2

As shown in the Test Report Ref. No. which forms part
of this Certificate

170500746SHA-001

This CB Test Certificate is issued by the National Certification Body

Intertek Semko AB
Box 1103
SE-164 22 Kista, Sweden
Int +46 8 750 00 00

Date: 27 September 2017

Intertek

Signature:

Gary Hu

Factories

GlobTek, Inc.
186 Veterans Drive, Northvale, NJ 07647, USA

GlobTek (Suzhou) Co., Ltd.
Building 4, No.76 JinLing East Road Suzhou Industrial Park Suzhou JiangSu, 215021 China

Shenzhen ENG Electronics Co., Ltd.
Block B2, A4 first floor, A4 third -four Floor of the East, Nuclear Industrial District, Baishixia Fuyun Town, Bao'an, Shenzhen, China

Additional information (if necessary)

Group differences for CENELEC countries and national differences for Singapore, Japan, China, Australia/New Zealand, Korea, USA and Canada are considered.

Explanation of type designation GT*46161-**-USB

The 1st symbol "*" can be "M" or "-" or "H" for market identification and not related to safety.

The 2nd symbol "**" denote the rated output wattage designation, which can be "01" to "16", with interval of 1.

The 3rd symbol "*" denote the standard rated output voltage designation, which can be "5.0" to "5.5" or "05" to "05.5" with interval of 0.1.

Model	Input	Output Voltage	Max. output current	Max. output power
GT*46161-*5.0-USB GT*46161-*05-USB	100-240V~, 50-60Hz,0.45A	5.0Vdc	3.2A	16W
GT*46161-**-USB (The 3rd "*" can be "5.1" to "5.5" or "05.1" to "05.5")	100-240V~, 50-60Hz,0.45A	5.1-5.5Vdc	3.14A	16W

Date: 27 September 2017

Signature: 