



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO.: 2019010907150484

Valid from: Oct.23,2023

Valid until: Oct.24,2027

**NAME AND REGISTERED
ADDRESS OF THE APPLICANT**

GlobTek,Inc.
186 Veterans Dr. Northvale, NJ 07647 / USA

**NAME AND REGISTERED
ADDRESS OF THE
MANUFACTURER**

GlobTek,Inc.
186 Veterans Dr. Northvale, NJ 07647 / USA

**NAME AND LOCATION
OF THE FACTORY**

GlobTek (Suzhou) Co.,Ltd.
Building 4, No. 76 JinLing East Road,Suzhou Industrial Park, Suzhou, JiangSu, China.

PRODUCT MODEL(S)

ITE POWER SUPPLY
See appendix (Altitude up to 5000m)

**STANDARDS AND
TECHNICAL REQUIREMENTS**

GB 17625.1-2022 (Class A) ;GB 4943.1-2022;GB/T 9254.1-2021

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification(REFNO. CNCA-C09-01:2023)

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

Date of original issued: Jan.16,2019

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P

The certificate information is available through the QR code below or CNCA's website: www.cnca.gov.cn



SIGNATURE:

谢肇煦



CHINA QUALITY CERTIFICATION CENTRE



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2019010907150484

page 1 of 1

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

GT*46161-**-** (The 1st symbol “*” denotes “M” or “-” or “H” for market identification and not related to safety. The 2nd symbol “*” denotes the rated output wattage designation, which can be “01” to “16” , with interval of 1. The 3rd symbol “*” denotes the standard rated output voltage designation, which can be “5.0” to “5.5” or “05” to “05.5” with interval of 0.1Vdc. The 4th symbol “*” =USB means Type 1 with USB*1 =USB1A means Type 2 with USB*1 =USB2A means Type 2 with USB*2 =USBC means Type 2 with USB Type C*1 =USB2C means Type 2 with USB Type C*2 =USB1A1C means Type 2 with USB*1 and USB Type C*1 The last symbol “*” denote any six character, which can be 0-9 or A-Z or ()[] or – or blank for marketing purposes.)

Input : 100-240V ~ , 50-60Hz ; 0.45A ;

Output : 5-5.5VDC ; MAX.3.2A

The output specifications are shown in the following table :

Model	DC output voltage	Max output current	Max output power
GT*46161-*5.0-**-**	5.0V	3.2A	16W
GT*46161-*05-**-**	5.0V	3.2A	16W
GT*46161-**-** (The 3rd symbol “*” denotes the standard rated output voltage designation, which can be “5.1” to “5.5” or “05.1” to “05.5” with interval of 0.1Vdc)	5.1-5.5V	3.14A	16W



CHINA QUALITY CERTIFICATION CENTRE