

## **Efficiency Level VI Report**

		GlobTek, Inc	
Model No.	GTM46161	GTM46161	
P/N:			
Engineer:			
Date Tested:			
Nameplate Specifications:			
Product Specifications	Input	Output	
Voltage(V)	100-240	5	
Current(A)		3.2	
Power(W)		16	
Frequency(Hz)	60-50Hz	60-50Hz	
Output Cord			
Type of Output Cord			
Revisions	Rev XX		

## List of Equipment used:

Equipment	Manufacturer	Description
Power Analyzer	Yokogawa	WT3000 Precision Power Analyzer
		Model 760302
		No: 91R225637
AC Source	IC.nroma	Programmable AC Source
		Model 61503
Electronic Load	Array	DC E-Load
		Model 3711A

Efficiency Level VI Limits				
	4 pt Average Efficiency (%)	No Load Power (W)		
DoE EL6 Limits	81.783%	0.1		
EU CoC Voluntary Tier 1 Limits	79.533%	0.15		
EU CoC Voluntary Tier 2 Limits	82.263%	0.075		
EU CoC Voluntary Tier 1 10% Eff Limits	69.963%			
EU CoC Voluntary Tier 2 10% Eff Limits	72.891%			

	Efficiency (%)	
Loading Condition	115Vac	230Vac
100% of rated FL	82.521%	84.262%
75% of rated FL	83.187%	84.612%
50% of rated FL	83.877%	84.828%
25% of rated FL	85.487%	85.550%
Average	83.768%	84.813%
-	No Load Power	
	115Vac	230Vac
Measured Power (W)	0.026	0.041
	10% Load Efficiency (%)	
	115Vac	230Vac
Efficiency (%)		