



Ref. Certif. No.

SE-89209

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

ITE POWER SUPPLY

Name and address of the applicant

GlobTek, Inc.
186 Veterans Drive, Northvale, NJ 07647 USA

Name and address of the manufacturer

Same as applicant

Name and address of the factory


Note: When more than one factory, please report on page 2

See page 2

Ratings and principal characteristics

Input: 100-240V~, 50-60Hz, 1.0A;
Output: 5-48VDC, Max. 6A, Max. 40W

Trademark (if any)



Customer's Testing Facility (CTF) Stage used

-

Model / Type Ref.

GT*46402-***

Additional information (if necessary may also be reported on page 2)

See page 2

A sample of the product was tested and found to be in conformity with

IEC 62368-1:2014

As shown in the Test Report Ref. No. which forms part of this Certificate

170800264SHA-001

This CB Test Certificate is issued by the National Certification Body

Intertek Semko AB
Box 1103
SE-164 22 Kista, Sweden
Int +46 8 750 00 00

Date: 8 December 2017



Signature:

Gary Hu

Factories

GlobTek, Inc.
186 Veterans Drive, Northvale, NJ 07647 USA

GlobTek (Suzhou) Co., Ltd.
Building 4, No.76 JinLing East Road, Suzhou Industrial Park, Suzhou, JiangSu, 215021 China

Additional information (if necessary)

Group difference for CENELEC countries and national differences USA and Canada are considered.

Model similarity:

Explanation of type designation GT*46402.***

The 1st symbol "*" can be 'M' or 'L' or 'H' for market identification and not related to safety.

The 2nd symbol "*" denotes the rated output wattage designation, which can be "01" to "40", with interval of 1W.

The 3rd symbol "*" denotes the standard rated output voltage designation, which can be "05" to "48" or "5.0" to "48.0", with interval of 0.1V.

The last symbol "*" denote any six character = 0-9 or A-Z or () [] or – or blank for marketing purposes

Model List:

Model	Input	Output voltage (Vdc)	Output current (A)	Max. output power (W)
GT*46402.***	100-240V~, 50-60Hz, 1.0A	5.0-8.9Vdc	6A	40W
		9.0-14.9Vdc	4.44A	40W
		15.0-24.0Vdc	2.66A	40W
		24.1-48.0Vdc	1.66A	40W

Date: 8 December 2017

Signature: 