



Ref. Certif. No.

SE-100244

**IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR
ELECTRICAL EQUIPMENT (IECEE) CB SCHEME**

CB TEST CERTIFICATE

Product

ITE Power Supply

Name and address of the applicant

GlobTek, Inc.
186 VETERANS DRIVE NORTHVALE
NJ 07647 United States

Name and address of the manufacturer

Same as applicant

Name and address of the factory

Note: When more than one factory, please report on page 2

See page 2

Ratings and principal characteristics

See page 2

Trademark (if any)



Customer's Testing Facility (CTF) Stage used

-

Model / Type Ref.

GT**-*****, GT*96600-*56***

Additional information (if necessary may also be
reported on page 2)

See page 2-3

A sample of the product was tested and found
to be in conformity with

IEC 60950-1:2005+A1+A2

As shown in the Test Report Ref. No. which forms part
of this Certificate

191100636SHA-001

This CB Test Certificate is issued by the National Certification Body

Intertek Semko AB
Torshamnsgatan 43
Box 1103
SE-164 22 Kista, Sweden

intertek

Signature:

Henrik Wikström

Date: 03 March, 2020

Factories

1. GlobTek (Suzhou) Co., Ltd Building 4, No. 76 JinLing East Road, Suzhou Industrial Park, Suzhou, JiangSu, 215021, China
2. GlobTek, Inc. 186 Veterans Dr. Northvale, NJ 07647 USA

Ratings and principal characteristics

GT**-*****: Input: 100-240V~, 50-60Hz, 1.5A;
Output: 5-54VDC, Max. 65W
GT*96600-*56***: Input: 100-240V~, 50-60Hz, 2.0A;
Output: 56VDC, Max. 70W

Additional information

Explanation of model GT**-*****

The 1st "*" part can be 'M' or '-' or 'H' for market identification and not related to safety.

The 2nd "*" can be 91099 or 96600 for market identification

The 3rd "*" denotes the rated output wattage designation, which can be "01" to "65", with interval of 1.

When the 2nd "*" = 91099

The 4th "*" denotes the standard rated output voltage designation, which can be "09", "15", "24", "48";

The 5th "*" is optional deviation, subtracted from standard output voltage, which can be "-0.01" to "-23.9" with interval of 0.01, or blank to indicate no voltage different.

The 4th "*" and 5th "*" together denote the output voltage, with a range of 5-48volts.

The 6th "*" =T2 means desktop class II with C8 AC inlet

=T2A means desktop class II with C18 AC inlet

=T3 means desktop class I or class II with functional earth with C14 AC inlet

=T3A means desktop class I or class II with functional earth with C6 AC inlet

=F means Open Frame class I or class II with functional earth

=FW means Open Frame class II

=P2 means Encapsulated class II

=P3 means Encapsulated class I or class II with functional earth

The last * denote any six character = 0-9 or A-Z or () or - or blank for marketing purposes.

When the 2nd "*" = 96600

The 4th "*" denote the standard rated output voltage designation, which can be "05" to "54" or "5.0" to "54.0" in 0.1V increments.

The 5th "*" =Blank

The 6th "*" =T2 means desktop class II with C8 AC inlet

=T2A means desktop class II with C18 AC inlet

=T3 means desktop class I or class II with functional earth with C14 AC inlet

=T3A means desktop class I or class II with functional earth with C6 AC inlet

=T2L means desktop class II with C8 AC inlet and housing with a DC jack

=T2AL means desktop class II with C18 AC inlet and housing with a DC jack

=T3L means desktop class I or class II with functional earth with C14 AC inlet and housing with a DC jack

=T3AL means desktop class I or class II with functional earth with C6 AC inlet and housing with a DC jack

=R2 means hybrid desktop housing class II with C8 AC inlet

=R3A means hybrid desktop housing class I or class II with functional earth with C6 AC inlet

=F means Open Frame class I or class II with functional earth

=FW means Open Frame class II

=P2 means Encapsulated class II

=P3 means Encapsulated class I or class II with functional earth

The last * denote any six character = 0-9 or A-Z or () or - or blank for marketing purposes.

Date: 03 March, 2020

Signature:



Explanation of model GT*96600-*56***

The 1st ^{“**”} part can be 'M' or '-' or 'H' for market identification and not related to safety.

The 2nd ^{“**”} denotes the rated output wattage designation, which can be “01” to “70”, with interval of 1.

The 3rd ^{“**”} =-T2 means desktop class II with C8 AC inlet

=-T2A means desktop class II with C18 AC inlet

=-T3 means desktop class I or class II with functional earth with C14 AC inlet

=-T3A means desktop class I or class II with functional earth with C6 AC inlet

The 4th ^{“**”} =-AP or -PP or -SP

-AP (with baby board) stands for Active POE

-PP (no baby board) stands for Passive POE

-SP (no baby board) stands for Simple POE

The last * denote any six character = 0-9 or A-Z or ()[] or – or blank for marketing purposes.

The group and national differences for CENELEC countries and Singapore, Japan, China, Australia/New Zealand, Korea, USA and Canada have been checked.

Date: 03 March, 2020

Signature:

