



Ref. Certif. No

NO125892

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

ICT/ITE POWER SUPPLY

Name and address of the applicant

GlobTek, Inc.
186 Veterans Drive
Northvale NJ 7647
United States of America

Name and address of the manufacturer

GlobTek, Inc.
186 Veterans Drive
Northvale NJ 7647
United States of America

Name and address of the factory

See next page(s)

Note: When more than one factory, please report on page 2

☒ Additional Information on Page 2Ratings and Principal characteristics
Trademark /Brand (If any)

INPUT: 100-240V~, 50-60Hz or 50/60Hz, 1.5A



Customer's Testing Facility (CTF) Stage used

Model/Type Ref

GTM91099-WWVV-X.X-AB*

Additional information (If necessary may also be reported on Page 2)

☒ Additional Information on Page 2

A sample of the product was tested and found to be in conformity with

IEC 62368-1:2018

As shown in the Test Report Ref. No. which forms part of this Certificate

REP003706

This CB Test Certificate is issued by the National Certification Body

Philip Pedersen vei 11,
NO-1366 Lysaker, Norway

Date: 27-02-2023

Signature: Juan Z Saussey
Certification department



Ref. Certif. No

NO125892

GlobTek, Inc.
186 Veterans Drive
Northvale NJ 7647
United States of America

GlobTek (Suzhou) Co., Ltd
Building 4, No. 76, Jin Ling East Rd., Suzhou Industrial Park,
Suzhou, JiangSu 215021
China

Additional Information (if necessary)

OUTPUT: refer to the test report. In model name, 'M' can be 'M' or '-' for market identification and not related to safety. 'WW' is the rated output wattage designation, with a maximum value of '60'. 'VV' is the standard rated output voltage designation, with a value of '09' '15' '24' and '48'. '-X.X' can be any number to denote the optional voltage deviation subtracted from standard rated output voltage in 0.1 volt increments, or blank to indicate the no voltage difference. 'VV-X.X' together denotes the voltage range 5V to 48V. 'A': T is External/Desktop model. 'B': When A=T, B can be 3, 3A, 2 or 2A, 3 means C14 inlet type, 3A means C6 inlet type, 2 means C8 inlet type, 2A means C8 inlet type. The last '*' denote any six character, which can be 0-9 or A-Z or () [] or – or blank for marketing purposes.



Philip Pedersen vei 11,
NO-1366 Lysaker, Norway
Date: 27-02-2023

Signature: Juan Z Saussey
Certification department